

Firestone

CONSTRUCTION TIRES

THE FORCE IN CONSTRUCTION TIRES

DURAFORCE™ DT

PREMIUM DESIGN FOR SUPERIOR PERFORMANCE



The DuraForce™ DT features premium bias construction specifically designed for skid steer, aerial lift, compact tele-handler and backhoe equipment.

Deep, extra-wide buttressed tread lugs made of cut-resistant compounds, deliver superior wear and value. The DuraForce DT contains 25% more working rubber than the popular DuraForce HD for extended wear and reduced operational costs.

Additional construction features include heavy-duty sidewall and large curb rib for more stability and puncture resistance, an aggressive rim deflector to help protect rim from damage and special tire compounds to help withstand cuts and punctures while operating in the most demanding conditions.

Tubeless				New Tire Dimensions (in.)			Max. Speed 5 mph	
Metric Size (Conventional Tire Size)	Article Number	Ply Rating	Rim Width	Overall Width	Overall Diameter	Bar Height	Max. Load & Infl. (lbs. @ psi)	Weight (lbs.)
215/70D15 (27x8.5 -15)	360-449	8	7.00	8.4	26.7	0.68	2880 @ 60	41
260/65D15 (27x10.5-15)	360-457	8	8.00	10.2	27.2	0.76	3120 @ 60	46
390/60D15 (31x15.50-15)	360-465	8	13.00	15.4	31.2	0.94	4360 @ 45	95
265/70D16.5 (10-16.5)	360-473	8	8.25	10.0	30.4	0.82	4140 @ 60	62
305/70D16.5 (12-16.5)	360-414	10	9.75	12.3	32.7	0.88	5600 @ 65	86
305/70D16.5 (12-16.5)	373-170	12	9.75	12.3	32.7	0.88	6320 @ 80	91
330/55D16.5 (31x13.00-16.5)	360-481	10	9.75	13.0	31.0	0.82	5300 @ 60	81
395/55D16.5 (33x15.50-16.5)	360-503	12	12.00	15.5	33.0	0.88	6835 @60	104

Deep-tread designed to deliver longer wear and traction in various work conditions.

Heavy-duty sidewall and large curb rib deliver more stability and greater puncture resistance.

Built to last with deep, wide buttressed tread lugs for longer tire life

Aggressive rim deflector keeps out debris to protect against rim damage and reduce flats and downtime.

Premium Bead Technology designed to prevent rim slip under high torque.

