

TABLE H1 — HIGH FLOTATION TIRES USED IN LOGGING SERVICE

TIRE TYPE NOMENCLATURE		MAX SPEED SPEED INDEX
TRA	TIRE TYPE	A2
HF-1	Shallow Tread	5 mph
HF-2	Regular Lug Tread	5 mph
HF-3	Deep Lug Tread	5 mph
HF-4	Extra Deep Lug Tread	5 mph

BASIC TIRE LOAD RATINGS FOR TIRE SELECTIONS

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES				
	psi		35	40	45	50	55
	kPa		240	280	310	340	380
54x37.00-25	lbs		13200 (12)				17100 (20)
	kg		5900 (12)				7700 (20)
66x43.00-25	lbs		19300 (14)			23400 (20)	
	kg		8800 (14)			10600 (20)	
66x43.00-26	lbs		19000 (14)				
	kg		8650 (14)				
67x34.00-25	lbs			20900 (14)			
	kg			9500 (14)			
67x34.00-26	lbs			20900 (14)			
	kg			9500 (14)			
68x50.00-32	lbs		19400 (16)				
	kg		8800 (16)				
DH73x44.00-32	lbs			24000 (16)		27600 (20)	
	kg			10900 (16)		12520 (20)	
76x50.00-32	lbs		25400 (16)				
	kg		11500 (16)				

NOTES:

1. Figures in parentheses denote ply rating for which load and inflation pressures are maximum.

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.