



PERFORMER EVO

Performer EVO is a radial tire that delivers several advantages over bias, including reduced inflation pressure, which helps lessen soil compaction for greater yields, and increased sidewall flex for an improved ride. All sizes are designed with R-1W tread depth that is approximately 25% deeper in the center compared with standard R-1 tread and offers traction in a variety of soil conditions. The Performer EVO includes a 6-year limited warranty*, as well as a field hazard and stubble policy.

PERFORMER EVO

- REDUCED INFLATION PRESSURE FOR IMPROVED SOIL COMPACTION OVER BIAS
- R-1W TREAD DEPTH FOR TRACTION IN A VARIETY OF SOIL CONDITIONS
- 6-YEAR LIMITED WARRANTY*



PERFORMER EVO TIRES

Material Description	Material Number	Full Size	Load Index	Speed Rating	Design Rim Width	Overall Diameter (in.)	Overall Width (in.)	Static Load Radius (in.)	Rolling Circumference (in.)	Rolling Circumference index	Bar Height 32nds	Bar Height (in.)	Flat Plate (Contact Area Sq. In.)	Max Load and Inflation (LBS @ PSI)
Performer EVO	3167	380/85R24	131	D	12.00	49.2	15.3	21.8	147	---	59	1.8	195	4300 @ 23
Performer EVO	6353	340/85R28	127	D	11.00	50.5	13.5	22.8	151	39	60	1.9	178	3860 @ 23
Performer EVO	3152	380/85R28	133	D	12.00	53.2	15.3	23.8	159	40	62	1.9	211	4540 @ 23
Performer EVO	7475	420/85R28	139	D	13.00	55.77	17.01	25	171	41	65	2.03	258	5360 @ 23
Performer EVO	7121	380/85R30	135	D	12.00	55.5	15.3	25.1	166	41	59	1.8	208	4800 @ 23
Performer EVO	7122	420/85R30	140	D	13.00	58.3	16.8	26.1	174	---	65	2.0	259	5520 @ 23
Performer EVO	7120	460/85R30	145	D	15.00	60.5	18.3	27.0	181	---	67	2.1	294	6400 @ 23
Performer EVO	8859	420/90R30	145	D	13.00	59.6	16.7	27.0	178	42	67	2.1	268	6400 @ 29
Performer EVO	7483	380/85R34	137	D	12.00	59.10	15.10	26.96	177	42	59	1.84	246	5080 @ 23
Performer EVO	6349	420/85R34	142	D	13.00	61.9	16.8	28.0	185	43	65	2.0	291	5840 @ 23
Performer EVO	3168	460/85R34	150	D	15.00	64.5	18.3	29.3	193	---	67	2.1	320	7400 @ 29
Performer EVO	3156	400/75R38	138	D	13.00	61.7	15.5	28.2	186	43	60	1.9	252	5200 @ 23
Performer EVO	5285	420/85R38	144	D	13.00	65.9	16.8	29.8	198	44	65	2.0	320	6150 @ 23
Performer EVO	3158	460/85R38	149	D	15.00	68.5	18.3	30.7	205	45	67	2.1	345	7150 @ 23

*Certain restrictions and limitations apply. See firestoneag.com for details.

PERFORMER EVO

LOAD AND INFLATION TABLES: TIRES USED AS SINGLES

Max. Speed 40 mph

Tire Load Limits at Various Cold Inflation Pressures

Tire Size	KG	40	60	80	100	120	140	160	180	200	240	280
	PSI	6	9	12	15	17	20	23	26	29		
340/85R28	KG	800	950	1120	1290	1450	1600	1750				
	LBS.	1760	2090	2470	2830	3200	3520	3860				
	LI NO.					121		127				
380/85R24	KG	875	1060	1250	1400	1600	1750	1950				
	LBS.	1930	2340	2760	3080	3520	3860	4300				
	LI NO.					124		131				
380/85R28	KG	950	1150	1320	1500	1700	1900	2060				
	LBS.	2090	2540	2910	3300	3740	4180	4540				
	LI NO.					126		133				
380/85R30	KG	975	1180	1360	1550	1750	1950	2180				
	LBS.	2150	2600	3000	3420	3860	4300	4800				
	LI NO.					127		135				
380/85R34	KG	40	60	80	100	120	140	160	180	200	240	280
	PSI	6	9	12	15	17	20	23	26	29	35	41
	KG	1030	1250	1450	1650	1850	2060	2300	2430	2500	2650	2900
	LBS.	2270	2760	3200	3640	4080	4540	5080	5360	5520	5840	6400
400/75R38	LI					129		137		140	142	145
	LBS.	2340	2830	3300	3740	4180	4680	5200				
	LI NO.					130		138				
420/85R28	KG	40	60	80	100	120	140	160				
	PSI	6	9	12	15	17	20	23				
	KG	1120	1320	1550	1750	2000	2240	2430				
	LBS.	2470	2910	3420	3860	4400	4940	5360				
420/85R30	LI					132		139				
	LBS.	2540	3000	3520	4080	4540	5080	5520				
	LI NO.					133		140				
420/85R34	KG	1220	1450	1700	1950	2180	2430	2650				
	LBS.	2680	3200	3740	4300	4800	5360	5840				
	LI NO.					135		142				
420/85R38	KG	1290	1550	1800	2060	2300	2580	2800				
	LBS.	2830	3420	3960	4540	5080	5680	6150				
	LI NO.					137		144				
420/90R30	KG	1215	1450	1700	1900	2180	2430	2650	2800	2900		
	LBS.	2680	3200	3740	4180	4800	5360	5840	6150	6400		
	LI NO.					135		142		145		
460/85R30	KG	1320	1600	1850	2120	2360	2650	2900				
	LBS.	2910	3520	4080	4680	5200	5840	6400				
	LI NO.					138		145				
460/85R34	KG	1400	1650	1950	2240	2500	2800	3080	3260	3360		
	LBS.	3080	3640	4300	4940	5520	6150	6800	7150	7400		
	LI NO.					140		147		150		
460/85R38	KG	1450	1750	2060	2360	2650	2900	3260				
	LBS.	3200	3860	4540	5200	5840	6400	7150				
	LI NO.					142		149				

Tires used as singles.

FOR MORE INFORMATION VISIT FIRESTONEAG.COM

