

TABLE H1 – HIGH FLOTATION TIRES USED IN LOGGING SERVICE

TIRE TYPE NOMENCLATURE		MAX SPEED
TRA	TIRE TYPE	SPEED INDEX A2
HF-1	Shallow Tread	5 mph
HF-2	Regular Lug Tread	5 mph
HF-3	Deep Lug Tread	5 mph
HF-4	Extra Deep Lug Tread	5 mph

BASIC TIRE LOAD RATINGS FOR TIRE SELECTIONS

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES					
	psi	35	40	45	50	55	60	
	kPa	240	280	310	340	380	415	
54x37.00B25	lbs	13200 (12)				17100 (20)		
	kg	5900 (12)				7700 (20)		
66x43.00-25	lbs	19300 (14)			23400 (20)			
	kg	8800 (14)			10600 (20)			
66x43.00-26	lbs	19000 (14)						
	kg	8650 (14)						
67x34.00B25	lbs		20900 (14)				26800 (22)	
	kg		9500 (14)				12150 (22)	
67x34.00-26	lbs		20900 (14)					
	kg		9500 (14)					
68x50.00-32	lbs	19400 (16)						
	kg	8800 (16)						
DH73x44.00B32	lbs		24000 (16)		27600 (20)			
	kg		10900 (16)		12500 (20)			
76x50.00B32	lbs	25400 (16)						
	kg	11500 (16)						

NOTES:

- Figures in parentheses denote ply rating for which load and inflation pressures are maximum.

RADIAL FARM

BIAS FARM

FRONTS &
IMPLEMENTS

FORESTRY &
FLOTATION

DISCONTINUED

LOAD & INFLATION
TABLES

GENERAL TIRE
INFORMATION

WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.