

TABLE R – DUPLEX FARM TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION MAXIMUM SPEED 30 MPH (50 KM/H)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES									
	psi	25	30	35	40	45	50	55	60	65	70	75
	kPa	170	210	240	280	310	340	380	410	450	480	520
36x16B17.5 NHS / 36x16-17.5 NHS	lbs	2910	3420	3960	4400 (8)	4800	5200	5520 (10)	5840	6150	6600	6950 (14)
	kg	1320	1550	1800	2000 (8)	2180	2360	2500 (10)	2650	2800	3000	3150 (14)
40x19B19.5 NHS	lbs	3640	4400	4940	5520	6000	6600 (12)	6950	7400	7850 (14)		
	kg	1650	2000	2240	2500	2725	3000 (12)	3150	3350	3550 (14)		

NOTES:

1. Figures in parentheses denote ply rating for which boldface loads and inflations are maximum.
2. Maximum shipping pressures are the maximum inflation pressures for the tire sizes and ply ratings shown.
3. For speeds not exceeding 10 mph (15 km/h), loads may be increased 15%.
4. For stationary service, loads may be increased by 100% with no increase in inflation pressure.

RADIAL FARM

BIAS FARM

FRONTS &
IMPLEMENTS

FORESTRY &
FLOTATION

DISCONTINUED

LOAD & INFLATION
TABLES

GENERAL TIRE
INFORMATION

WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.