

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

TIRE TYPE NOMENCLATURE		MAX SPEED	
TRA	TIRE TYPE	A8/B	D
R-1	Drive Wheel, Regular Tread	30 mph	40 mph
R-1W	Drive Wheel, Wet Traction Tread	30 mph	40 mph
R-2	Cane & Rice, Drive Wheel, Deep Tread	25 mph	—

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION Symbol	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
		LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI															
230/95R48	LI						114		121		123	126	129	132	134		
	SINGLES		1430	1710	2040	2270	2600	2910	3200	3300	3420	3740	4080	4400	4680		
	DUALS		1260	1500	1800	2000	2290	2560	2820	2900	3010	3290	3590	3870	4120		
280/70R16	LI						95		102		108	112					
	SINGLES		855	1020	1200	1360	1520	1710	1870	2040	2200	2470					
	DUALS		750	900	1060	1200	1340	1500	1650	1800	1940	2170					
28070R18	LI						97		104		110	114					
	SINGLES		910	1070	1280	1430	1610	1820	1980	2150	2340	2600					
	DUALS		800	940	1130	1260	1420	1600	1740	1890	2060	2290					
280/70R20	LI						99		106		112	116					
	SINGLES		935	1140	1320	1520	1710	1870	2090	2270	2470	2760					
	DUALS		820	1000	1160	1340	1500	1650	1840	2000	2170	2430					
280/85R24	LI						108		115								
	SINGLES		1230	1480	1710	1930	2200	2470	2680								
	DUALS		1080	1300	1500	1700	1940	2170	2360								
290/95R34	LI						119		125		129	131					
	SINGLES		1650	2040	2340	2680	3000	3300	3640	3860	4080	4300					
	DUALS		1450	1800	2060	2360	2640	2900	3200	3400	3590	3780					
300/70R20	LI						102		110		116	120					
	SINGLES		1050	1280	1480	1650	1870	2090	2340	2540	2760	3080					
	DUALS		920	1130	1300	1450	1650	1840	2060	2240	2430	2710					
320/85R24	LI						115		122								
	SINGLES		1480	1820	2090	2400	2680	3000	3300								
	DUALS		1300	1600	1840	2110	2360	2640	2900								
320/85R28	LI						118		124								
	SINGLES		1610	1930	2270	2600	2910	3200	3520								
	DUALS		1420	1700	2000	2290	2560	2820	3100								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

TIRE TYPE NOMENCLATURE		MAX SPEED SPEED INDEX	
TRA	TIRE TYPE	A&B	D
R-1	Drive Wheel, Regular Tread	50 km/h	65 km/h
R-1W	Drive Wheel, Wet Traction Tread	50 km/h	65 km/h
R-2	Cane & Rice, Drive Wheel, Deep Tread	40 km/h	—

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	kPa		40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
	bar		0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
230/95R48		LI					114		121		123	126	129	132	134		
	SINGLES		650	775	925	1030	1180	1320	1450	1500	1550	1700	1850	2000	2120		
	DUALS		570	680	810	910	1040	1160	1280	1320	1360	1500	1630	1760	1870		
	TRIPLES		530	640	760	840	970	1080	1190	1230	1270	1390	1520	1640	1740		
280/70R16		LI					95		102		108	112					
	SINGLES		387	462	545	615	690	775	850	925	1000	1120					
	DUALS		340	410	480	540	610	680	750	810	880	990					
	TRIPLES		320	380	450	500	570	640	700	760	820	920					
280/70R18		LI					97		104		110	114					
	SINGLES		412	487	580	650	730	825	900	975	1060	1180					
	DUALS		360	430	510	570	640	730	790	860	930	1040					
	TRIPLES		340	400	480	530	600	680	740	800	870	970					
280/70R20		LI					99		106		112	116					
	SINGLES		425	515	600	690	775	850	950	1030	1120	1250					
	DUALS		370	450	530	610	680	750	840	910	990	1100					
	TRIPLES		350	420	490	570	640	700	780	840	920	1030					
280/85R24		LI					108		115								
	SINGLES		560	670	775	875	1000	1120	1215								
	DUALS		490	590	680	770	880	990	1070								
	TRIPLES		460	550	640	720	820	920	1000								
290/95R34		LI					119		125		129	131					
	SINGLES		750	925	1060	1215	1360	1500	1650	1750	1850	1950					
	DUALS		660	810	930	1070	1200	1320	1450	1540	1630	1720					
	TRIPLES		620	760	870	1000	1120	1230	1350	1440	1520	1600					
300/70R20		LI					102		110		116	120					
	SINGLES		475	580	670	750	850	950	1060	1150	1250	1400					
	DUALS		420	510	590	660	750	840	930	1010	1100	1230					
	TRIPLES		390	480	550	620	700	780	870	940	1030	1150					
320/85R24		LI					115		122								
	SINGLES		670	825	950	1090	1215	1360	1500								
	DUALS		590	730	840	960	1070	1200	1320								
	TRIPLES		550	680	780	890	1000	1120	1230								
320/85R28		LI					118		124								
	SINGLES		730	875	1030	1180	1320	1450	1600								
	DUALS		640	770	910	1040	1160	1280	1410								
	TRIPLES		600	720	840	970	1080	1190	1310								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM
 BIAS FARM
 FRONTS & IMPLEMENTS
 FORESTRY & FLOTATION
 DISCONTINUED
 LOAD & INFLATION TABLES
 GENERAL TIRE INFORMATION
 WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																	
320/85R34		LI					121		127		131	133					
	SINGLES		1760	2150	2470	2830	3200	3520	3860	4080	4300	4540					
	DUALS		1550	1890	2170	2490	2820	3100	3400	3590	3780	4000					
	TRIPLES		1440	1760	2030	2320	2620	2890	3170	3350	3530	3720					
320/85R38		LI					123		129		133	135	138	141	143		
	SINGLES		1870	2270	2600	3000	3420	3740	4080	4300	4540	4800	5200	5680	6000		
	DUALS		1650	2000	2290	2640	3010	3290	3590	3780	4000	4220	4580	5000	5280		
	TRIPLES		1530	1860	2130	2460	2800	3070	3350	3530	3720	3940	4260	4660	4920		
320/90R42		LI					126		133		136	139					
	SINGLES		2090	2470	2910	3300	3740	4180	4540	4800	4940	5360					
	DUALS		1840	2170	2560	2900	3290	3680	4000	4220	4350	4720					
	TRIPLES		1710	2030	2390	2710	3070	3430	3720	3940	4050	4400					
320/90R46		LI					127		135		138	140	144	146	148		
	SINGLES		2150	2600	3000	3420	3860	4300	4800	5080	5200	5520	6150	6600	6950		
	DUALS		1890	2290	2640	3010	3400	3780	4220	4470	4580	4860	5410	5810	6120		
	TRIPLES		1760	2130	2460	2800	3170	3530	3940	4170	4260	4530	5040	5410	5700		
320/90R50		LI					129		136		140	142	145	148			
	SINGLES		2270	2760	3200	3640	4080	4540	4940	5200	5520	5840	6400	6950			
	DUALS		2000	2430	2820	3200	3590	4000	4350	4580	4860	5140	5630	6120			
	TRIPLES		1860	2260	2620	2980	3350	3720	4050	4260	4530	4790	5250	5700			
320/90R54		LI					131		138		141	143	146	149			
	SINGLES		2340	2830	3300	3740	4300	4680	5200	5520	5680	6000	6600	7150			
	DUALS		2060	2490	2900	3290	3780	4120	4580	4860	5000	5280	5810	6290			
	TRIPLES		1920	2320	2710	3070	3530	3840	4260	4530	4660	4920	5410	5860			
340/85R24		LI					119		125								
	SINGLES		1650	1980	2270	2600	3000	3300	3640								
	DUALS		1450	1740	2000	2290	2640	2900	3200								
	TRIPLES		1350	1620	1860	2130	2460	2710	2980								
340/85R28		LI					121		127								
	SINGLES		1760	2090	2470	2830	3200	3520	3860								
	DUALS		1550	1840	2170	2490	2820	3100	3400								
	TRIPLES		1440	1710	2030	2320	2620	2890	3170								
360/70R20		LI					113		120		125	129					
	SINGLES		1390	1650	1930	2200	2540	2760	3080	3300	3640	4080					
	DUALS		1220	1450	1700	1940	2240	2430	2710	2900	3200	3590					
	TRIPLES		1140	1350	1580	1800	2080	2260	2530	2710	2980	3350					
360/70R28		LI					118		125								
	SINGLES		1610	1930	2270	2600	2910	3300	3640								
	DUALS		1420	1700	2000	2290	2560	2900	3200								
	TRIPLES		1320	1580	1860	2130	2390	2710	2990								
380/70R24		LI					119		125								
	SINGLES		1650	1980	2270	2600	3000	3300	3640								
	DUALS		1450	1740	2000	2290	2640	2900	3200								
	TRIPLES		1350	1620	1860	2130	2460	2710	2980								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
320/85R34	LI							121		127		131	133				
	SINGLES		800	975	1120	1285	1450	1600	1750	1850	1950	2060					
	DUALS		700	860	990	1130	1280	1410	1540	1630	1720	1810					
	TRIPLES		660	800	920	1050	1190	1310	1440	1520	1600	1690					
320/85R38	LI						123		129		133	135	138	141	143		
	SINGLES		850	1030	1180	1360	1550	1700	1850	1950	2060	2180	2360	2575	2725		
	DUALS		750	910	1040	1200	1360	1500	1630	1720	1810	1920	2080	2270	2400		
	TRIPLES		700	840	970	1120	1270	1390	1520	1600	1690	1790	1940	2110	2230		
320/90R42	LI						126		133		136	139					
	SINGLES		950	1120	1320	1500	1700	1900	2060	2180	2240	2430					
	DUALS		840	990	1160	1320	1500	1670	1810	1920	1970	2140					
	TRIPLES		780	920	1080	1230	1390	1560	1690	1790	1840	1990					
320/90R46	LI						127		135		138	140	144	146	148		
	SINGLES		975	1180	1360	1550	1750	1950	2180	2300	2360	2500	2800	3000	3150		
	DUALS		860	1040	1200	1360	1540	1720	1920	2020	2080	2200	2460	2640	2770		
	TRIPLES		800	970	1120	1270	1440	1600	1790	1890	1940	2050	2300	2460	2580		
320/90R50	LI						129		136		140	142	145	148			
	SINGLES		1030	1250	1450	1650	1850	2060	2240	2360	2500	2650	2900	3150			
	DUALS		910	1100	1280	1450	1630	1810	1970	2080	2200	2330	2550	2770			
	TRIPLES		840	1030	1190	1350	1520	1690	1840	1940	2050	2170	2380	2580			
320/90R54	LI						131		138		141	143	146	149			
	SINGLES		1060	1285	1500	1700	1950	2120	2360	2500	2575	2725	3000	3250			
	DUALS		930	1130	1320	1500	1720	1870	2080	2200	2270	2400	2640	2860			
	TRIPLES		870	1050	1230	1390	1600	1740	1940	2050	2110	2230	2460	2670			
340/85R24	LI						119		125								
	SINGLES		750	900	1030	1180	1360	1500	1650								
	DUALS		660	790	910	1040	1200	1320	1450								
	TRIPLES		620	740	840	970	1120	1230	1350								
340/85R28	LI						121		127								
	SINGLES		800	950	1120	1285	1450	1600	1750								
	DUALS		700	840	990	1130	1280	1410	1540								
	TRIPLES		660	780	920	1050	1190	1310	1440								
360/70R20	LI						113		120		125	129					
	SINGLES		630	750	875	1000	1150	1250	1400	1500	1650	1850					
	DUALS		550	660	770	880	1010	1100	1230	1320	1450	1630					
	TRIPLES		520	620	720	820	940	1030	1150	1230	1350	1520					
360/70R28	LI						118		125								
	SINGLES		730	875	1030	1180	1320	1500	1650								
	DUALS		640	770	910	1040	1160	1320	1450								
	TRIPLES		600	720	850	970	1080	1230	1350								
380/70R24	LI						119		125								
	SINGLES		750	900	1030	1180	1360	1500	1650								
	DUALS		660	790	910	1040	1200	1320	1450								
	TRIPLES		620	740	840	970	1120	1230	1350								

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
	LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
380/70R28	LI							121		127							
	SINGLES		1760	2090	2470	2830	3200	3520	3860								
	DUALS		1550	1840	2170	2490	2820	3100	3400								
	TRIPLES		1440	1710	2030	2320	2620	2890	3170								
380/80R38	LI						130		137		140	142					
	SINGLES		2270	2760	3200	3640	4180	4540	5080	5360	5520	5840					
	DUALS		2000	2430	2820	3200	3680	4000	4470	4720	4860	5140					
	TRIPLES		1860	2260	2620	2980	3430	3720	4170	4400	4530	4790					
380/85R24	LI						124		131								
	SINGLES		1930	2340	2760	3080	3520	3860	4300								
	DUALS		1700	2060	2430	2710	3100	3400	3780								
	TRIPLES		1580	1920	2260	2530	2890	3170	3530								
380/85R26	LI						125		132								
	SINGLES		2040	2400	2830	3200	3640	4080	4400								
	DUALS		1800	2110	1780	2820	3200	3590	3870								
	TRIPLES		1670	1970	2320	2620	2980	3350	3610								
380/85R28	LI						126		133								
	SINGLES		2090	2540	2910	3300	3740	4180	4540								
	DUALS		1840	2240	2560	2900	3290	3680	4000								
	TRIPLES		1710	2080	2390	2710	3070	3430	3720								
380/85R30	LI						127		135								
	SINGLES		2150	2600	3000	3420	3860	4300	4800								
	DUALS		1890	2290	2640	3010	3400	3780	4220								
	TRIPLES		1760	2130	2460	2800	3170	3530	3940								
380/85R34	LI						129		137		140	142	145				
	SINGLES		2270	2760	3200	3640	4080	4540	5080	5360	5520	5840	6400				
	DUALS		2000	2430	2820	3200	3590	4000	4470	4720	5860	5140	5630				
	TRIPLES		1860	2260	2620	2980	3350	3720	4170	4400	4530	4790	5250				
385/85R34	LI						130		138		141	143	146				
	SINGLES		2340	2830	3300	3740	4180	4680	5200	5360	5680	6000	6600				
	DUALS		2060	2490	2900	3290	3680	4120	4580	4720	5000	5280	5810				
	TRIPLES		1920	2320	2710	3070	3430	3840	4260	4400	4660	4920	5410				
380/90R46	LI						137		144		147	149	152				
	SINGLES		2830	3300	3860	4400	5080	5520	6150	6400	6800	7150	7850				
	DUALS		2490	2900	3400	3870	4470	4860	5410	5630	5980	6290	6910				
	TRIPLES		2320	2710	3170	3610	4170	4530	5040	5250	5580	5860	6440				
380/90R50	LI						138		145		148	151					
	SINGLES		2910	3520	4080	4680	5200	5840	6400	6800	6950	7600					
	DUALS		2560	3100	3590	4120	4580	5140	5630	5980	6120	6690					
	TRIPLES		2390	2890	3350	3840	4260	4790	5250	5580	5700	6230					
380/90R54	LI						140		146		150	152					
	SINGLES		3000	3640	4300	4800	5520	6000	6600	6950	7400	7850					
	DUALS		2640	3200	3780	4220	4860	5280	5810	6120	6510	6910					
	TRIPLES		2460	2980	3530	3940	4530	4920	5410	5700	6070	6440					

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
380/70R28		LI						121	127								
	SINGLES		800	950	1120	1285	1450	1600	1750								
	DUALS		700	840	990	1130	1280	1410	1540								
	TRIPLES		660	780	920	1050	1190	1310	1440								
380/80R38		LI					130	137		140	142						
	SINGLES		1030	1250	1450	1650	1900	2060	2300	2430	2500	2650					
	DUALS		910	1100	1280	1450	1670	1810	2020	2140	2200	2330					
	TRIPLES		840	1030	1190	1350	1560	1690	1890	1990	2050	2170					
380/85R24		LI					124	131									
	SINGLES		875	1060	1250	1400	1600	1750	1950								
	DUALS		770	930	1100	1230	1410	1540	1720								
	TRIPLES		720	870	1030	1150	1310	1440	1600								
380/85R26		LI					125	132									
	SINGLES		925	1090	1285	1450	1650	1850	2000								
	DUALS		810	960	1130	1280	1450	1630	1760								
	TRIPLES		760	890	1050	1190	1350	1520	1640								
380/85R28		LI					126	133									
	SINGLES		950	1150	1320	1500	1700	1900	2060								
	DUALS		840	1010	1160	1320	1500	1670	1810								
	TRIPLES		780	940	1080	1230	1390	1560	1690								
380/85R30		LI					127	135									
	SINGLES		975	1180	1360	1550	1750	1950	2180								
	DUALS		860	1040	1200	1360	1540	1720	1920								
	TRIPLES		800	970	1120	1270	1440	1600	1790								
380/85R34		LI					129	137		140	142	145					
	SINGLES		1030	1250	1450	1650	1850	2060	2300	2430	2500	2650	2900				
	DUALS		910	1100	1280	1450	1630	1810	2020	2140	2200	2330	2550				
	TRIPLES		840	1030	1190	1350	1520	1690	1890	1990	2050	2170	2380				
385/85R34		LI					130	138		141	143	146					
	SINGLES		1060	1285	1500	1700	1900	2120	2360	2430	2575	2725	3000				
	DUALS		930	1130	1320	1500	1670	1870	2080	2140	2270	2400	2640				
	TRIPLES		870	1050	1230	1390	1560	1740	1940	1990	2110	2230	2460				
380/90R46		LI					137	144		147	149	152					
	SINGLES		1285	1500	1750	2000	2300	2500	2800	2900	3075	3250	3550				
	DUALS		1130	1320	1540	1760	2020	2200	2460	2550	2710	2860	3120				
	TRIPLES		1050	1230	1440	1640	1890	2050	2300	2380	2520	2670	2910				
380/90R50		LI					138	145		148	151						
	SINGLES		1320	1600	1850	2120	2360	2650	2900	3075	3150	3450					
	DUALS		1160	1410	1630	1870	2080	2330	2550	2710	2770	3040					
	TRIPLES		1080	1310	1520	1740	1940	2170	2380	2520	2580	2830					
380/90R54		LI					140	146		150	152						
	SINGLES		1360	1650	1950	2180	2500	2725	3000	3150	3350	3550					
	DUALS		1200	1450	1720	1920	2200	2400	2640	2770	2950	3120					
	TRIPLES		1120	1350	1600	1790	2050	2230	2460	2580	2750	2910					

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION psi Symbol	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
		6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
380/105R50	LI					129		137			140	142	145			
	SINGLES	3300	3960	4680	5360	6000	6600	7400	7600	8050	8550	9350	10200	10700	11400	12300
	DUALS	2900	3480	4120	4720	5280	5810	6510	6690	7080	7520	8230	8980	9420	10030	10825
	TRIPLES	2710	3250	3840	4400	4920	5410	6070	6230	6600	7010	7670	8360	8770	9350	10085
380/85R34	LI					130		138								
	SINGLES	2270	2760	3200	3640	4080	4540	5080	5360	5520	5840	6400				
	DUALS	2000	2430	1820	3200	3590	4000	4470	4720	4860	5140	5630				
	TRIPLES	1860	2260	2620	2980	3350	3720	4170	4400	4530	4790	5250				
400/75R38	LI					130		138								
	SINGLES	2340	2830	3300	3740	4180	4680	5200								
	DUALS	2060	2490	2900	3290	3670	4120	4580								
	TRIPLES	1920	2320	2700	3070	3430	3840	4260								
420/70R24	LI					123		130								
	SINGLES	1930	2270	2680	3080	3420	3860	4180								
	DUALS	1700	2000	2360	2710	3010	3400	3680								
	TRIPLES	1580	1860	2200	2530	2800	3170	3430								
420/80R46	LI					139		145		149	151	154	156	159	161	
	SINGLES	2910	3520	4080	4680	5360	5840	6400	6800	7150	7600	8250	8800	9650	10200	
	DUALS	2560	3100	3590	4120	4720	5140	5630	5980	6290	6690	7260	7740	8490	8980	
	TRIPLES	2390	2890	3350	3840	4400	4790	5250	5580	5860	6230	6770	7220	7910	8360	
420/85R24	LI					129		137								
	SINGLES	2270	2760	3200	3640	4080	4540	5080								
	DUALS	2000	2430	2820	3200	3590	4000	4470								
	TRIPLES	1860	2260	2620	2980	3350	3720	4170								
420/85R26	LI					131		138								
	SINGLES	2340	2830	3300	3740	4300	4680	5200								
	DUALS	2060	2490	2900	3290	3780	4120	4580								
	TRIPLES	1920	2320	2710	3070	3530	3840	4260								
420/85R28	LI					132		139								
	SINGLES	2470	2910	3420	3860	4400	4940	5360								
	DUALS	2170	2560	3010	3400	3870	4350	4720								
	TRIPLES	2030	2390	2800	3170	3610	4050	4400								
420/85R30	LI					133		140								
	SINGLES	2540	3000	3520	4080	4540	5080	5520								
	DUALS	2240	2640	3100	3590	4000	4470	4860								
	TRIPLES	2080	2460	2890	3350	3720	4170	4530								
420/85R34	LI					135		142		145	147					
	SINGLES	2680	3200	3740	4300	4800	5360	5840	6150	6400	6800					
	DUALS	2360	2820	3290	3780	4220	4720	5140	5410	5630	5980					
	TRIPLES	2200	2620	3070	3530	3940	4400	4790	5040	5250	5580					
420/85R38	LI					137		144								
	SINGLES	2830	3420	3960	4540	5080	5680	6150								
	DUALS	2490	3010	3480	4000	4470	5000	5410								
	TRIPLES	2320	2800	3250	3720	4170	4660	5040								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
		LI					143	150		153	155	158	161	163	165	168	
380/105R50	SINGLES		1500	1800	2120	2430	2725	3000	3350	3450	3650	3875	4250	4625	4875	5150	5600
	DUALS		1320	1580	1870	2140	2400	2640	2950	3040	3210	3410	3740	4070	4290	4530	4930
	TRIPLES		1230	1480	1740	1990	2230	2460	2750	2830	2990	3180	3490	3790	4000	4220	4590
380/85R34	SINGLES		1030	1250	1450	1650	1850	2060	2300	2430	2500	2650	2900				
	DUALS		910	1100	1280	1450	1630	1810	2020	2140	2200	2330	2550				
	TRIPLES		850	1030	1190	1350	1520	1690	1890	1990	2050	2170	2380				
400/75R38	SINGLES		1060	1285	1500	1700	1900	2120	2360								
	DUALS		930	1130	1320	1500	1670	1870	2080								
	TRIPLES		870	1050	1230	1390	1620	1740	1940								
420/70R24	SINGLES		875	1030	1215	1400	1550	1750	1900								
	DUALS		770	910	1070	1230	1360	1540	1670								
	TRIPLES		720	840	1000	1150	1270	1440	1560								
420/80R46	SINGLES		1320	1600	1850	2120	2430	2650	2900	3075	3250	3450	3750	4000	4375	4625	
	DUALS		1160	1410	1630	1870	2140	2330	2550	2710	2860	3040	3300	3520	3850	4070	
	TRIPLES		1080	1310	1520	1740	1990	2170	2380	2520	2670	2830	3080	3280	3590	3790	
420/85R24	SINGLES		1030	1250	1450	1650	1850	2060	2300								
	DUALS		910	1100	1280	1450	1630	1810	2020								
	TRIPLES		840	1030	1190	1350	1520	1690	1890								
420/85R26	SINGLES		1060	1285	1500	1700	1950	2120	2360								
	DUALS		930	1130	1320	1500	1720	1870	2080								
	TRIPLES		870	1050	1230	1390	1600	1740	1940								
420/85R28	SINGLES		1120	1320	1550	1750	2000	2240	2430								
	DUALS		990	1160	1360	1540	1760	1970	2140								
	TRIPLES		920	1080	1270	1440	1640	1840	1990								
420/85R30	SINGLES		1150	1360	1600	1850	2060	2300	2500								
	DUALS		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES		940	1120	1310	1520	1690	1890	2050								
420/85R34	SINGLES		1215	1450	1700	1950	2180	2430	2650	2800	2900	3075					
	DUALS		1070	1280	1500	1720	1920	2140	2330	2460	2550	2710					
	TRIPLES		1000	1190	1390	1600	1790	1990	2170	2300	2380	2520					
420/85R38	SINGLES		1285	1550	1800	2060	2300	2575	2800								
	DUALS		1130	1360	1580	1810	2020	2270	2460								
	TRIPLES		1050	1270	1480	1690	1890	2110	2300								

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																	
420/90R30		LI					135		142								
	SINGLES		2680	3200	3740	4180	4800	5360	5840	6150	6400						
	DUALS		2360	2820	3290	3680	4220	4720	5140	5410	5630						
	TRIPLES		2200	2620	3070	3430	3940	4400	4790	5040	5250						
440/65R24		LI					123										
	SINGLES		1870	2270	2600	3000	3420	3740	3960								
	DUALS		1650	2000	2290	2640	3010	3290	3480								
	TRIPLES		1530	1860	2130	2460	2800	3070	3250								
440/65R28		LI					125		131								
	SINGLES		2040	2400	2830	3200	3640	3960	4300								
	DUALS		1800	2110	2490	2820	3200	3490	3780								
	TRIPLES		1670	1970	2320	2620	2990	3250	3530								
460/85R30		LI					138		145								
	SINGLES		2910	3520	4080	4680	5200	5840	6400								
	DUALS		2560	3100	3590	4120	4580	5140	5630								
	TRIPLES		2390	2890	3350	3840	4260	4790	5250								
460/85R34		LI					140	144	147								
	SINGLES		3080	3640	4300	4940	5520	6150	6800								
	DUALS		2710	3200	3780	4350	4860	5410	5980								
	TRIPLES		2530	2980	3530	4050	4530	5040	5580								
460/85R38		LI					142		149								
	SINGLES		3200	3860	4540	5200	5840	6400	7150								
	DUALS		2820	3400	4000	4580	5140	5630	6290								
	TRIPLES		2620	3170	3720	4260	4790	5250	5860								
460/85R42		LI					144		150								
	SINGLES		3420	4080	4800	5360	6150	6800	7400								
	DUALS		3010	3590	4220	4720	5410	5980	6510								
	TRIPLES		2800	3350	3940	4400	5040	5580	6070								
480/85R24		LI					127		133			137	140				
	SINGLES		2150	2600	3000	3420	3860	4180	4540	4800	5080	5520					
	DUALS		1890	2290	2640	3010	3400	3680	4000	4220	4470	4860					
	TRIPLES		1760	2130	2460	2800	3170	3430	3720	3940	4170	4530					
480/65R28		LI					130		136								
	SINGLES		2270	2760	3200	3640	4180	4540	4940								
	DUALS		2000	2430	2820	3200	3680	4000	4350								
	TRIPLES		1860	2260	2620	2990	3430	3720	4051								
480/70R24		LI					131		138								
	SINGLES		2340	2830	3300	3740	4300	4680	5200								
	DUALS		2060	2490	2900	3290	3780	4120	4580								
	TRIPLES		1920	2320	2710	3070	3530	3840	4260								
480/70R28		LI					133		140								
	SINGLES		2540	3000	3520	4080	4540	5080	5520								
	DUALS		2240	2640	3100	3590	4000	4470	4860								
	TRIPLES		2080	2460	2890	3350	3720	4170	4530								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	kPa		40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
	bar		0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
420/90R30		LI							135		142						
	SINGLES		1215	1450	1700	1900	2180	2430	2650	2800	2900						
	DUALS		1070	1280	1500	1670	1920	2140	2330	2460	2550						
	TRIPLES		1000	1190	1390	1560	1790	1990	2170	2300	2380						
440/65R24		LI							123								
	SINGLES		850	1030	1180	1360	1550	1700	1800								
	DUALS		750	910	1040	1200	1360	1500	1580								
	TRIPLES		700	850	970	1120	1270	1390	1480								
440/65R28		LI							125		131						
	SINGLES		925	1090	1285	1450	1650	1800	1950								
	DUALS		810	960	1130	1280	1450	1580	1720								
	TRIPLES		760	890	1050	1190	1350	1480	1600								
460/85R30		LI							138		145						
	SINGLES		1320	1600	1850	2120	2360	2650	2900								
	DUALS		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES		1080	1310	1520	1740	1940	2170	2380								
460/85R34		LI							140	144	147						
	SINGLES		1400	1650	1950	2240	2500	2800	3075								
	DUALS		1230	1450	1720	1970	2200	2460	2710								
	TRIPLES		1150	1350	1600	1840	2050	2300	2520								
460/85R38		LI							142		149						
	SINGLES		1450	1750	2060	2360	2650	2900	3250								
	DUALS		1280	1540	1810	2080	2330	2550	2860								
	TRIPLES		1190	1440	1690	1940	2170	2380	2670								
460/85R42		LI							144		150						
	SINGLES		1550	1850	2180	2430	2800	3075	3350								
	DUALS		1360	1630	1920	2140	2460	2710	2950								
	TRIPLES		1270	1520	1790	1990	2300	2520	2750								
480/85R24		LI							127		133		137	140			
	SINGLES		975	1180	1360	1550	1750	1900	2060	2180	2300	2500					
	DUALS		860	1040	1200	1360	1540	1670	1810	1920	2020	2200					
	TRIPLES		800	970	1120	1270	1440	1560	1690	1790	1890	2050					
480/65R28		LI							130		136						
	SINGLES		1030	1250	1450	1650	1900	2060	2240								
	DUALS		910	1100	1280	1450	1670	1810	1970								
	TRIPLES		850	1030	1190	1350	1560	1690	1840								
480/70R24		LI							131		138						
	SINGLES		1060	1285	1500	1700	1950	2120	2360								
	DUALS		930	1130	1320	1500	1720	1870	2080								
	TRIPLES		870	1050	1230	1390	1600	1740	1940								
480/70R28		LI							133		140						
	SINGLES		1150	1360	1600	1850	2060	2300	2500								
	DUALS		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES		940	1120	1310	1520	1690	1890	2050								

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
	LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
480/70R30	LI						134		141			145	147	150	152		
	SINGLES		2600	3080	3640	4180	4680	5200	5680	6000	6400	6800	7400	7850			
	DUALS		2290	2710	3200	3680	4120	4580	5000	5280	5630	5980	6510	6910			
	TRIPLES		2130	2530	2980	3430	3840	4260	4660	4920	5250	5580	6070	6440			
480/70R34	LI						136		143			146	149	152	155		
	SINGLES		2760	3300	3860	4400	4940	5520	6000	6400	6600	7150	7850	8550			
	DUALS		2430	2900	3400	3870	4350	4860	5280	5630	5810	6290	6910	7520			
	TRIPLES		2260	2710	3170	3610	4050	4530	4920	5250	5410	5860	6440	7010			
480/70R38	LI						138		145								
	SINGLES		2910	3520	4080	4680	5200	5840	6400								
	DUALS		2560	3100	3590	4120	4580	5140	5630								
	TRIPLES		2390	2890	3350	3840	4260	4790	5250								
480/80R30	LI						139		145			149	151	154	156	159	
	SINGLES		2910	3520	4080	4680	5360	5840	6400	6800	7150	7600	8250	8800	9650		
	DUALS		2560	3100	3590	4120	4720	5140	5630	5980	6290	6690	7260	7740	8490		
	TRIPLES		2390	2890	3350	3840	4400	4790	5250	5580	5860	6230	6770	7220	7910		
480/80R38	LI						142		149								
	SINGLES		3300	3960	4540	5200	5840	6600	7150								
	DUALS		2900	3480	4000	4580	5140	5810	6290								
	TRIPLES		2710	3250	3720	4260	4790	5410	5860								
480/80R42	LI						144		151			154					
	SINGLES		3420	4080	4800	5520	6150	6950	7600	8050	8250						
	DUALS		3010	3590	4220	4860	5410	6120	6690	7080	7260						
	TRIPLES		2800	3350	3940	4530	5040	5700	6230	6600	6770						
480/80R46	LI						145		152			155	158				
	SINGLES		3640	4300	5080	5680	6400	7150	7850	8250	8550	9350					
	DUALS		3200	3780	4470	5000	5630	6290	6910	7260	7520	8230					
	TRIPLES		2980	3530	4170	4660	5250	5860	6440	6770	7010	7670					
480/80R50	LI						147		154			157	159				
	SINGLES		3740	4540	5200	6000	6800	7600	8250	8550	9100	9650					
	DUALS		3290	4000	4580	5280	5980	6690	7260	7520	8010	8490					
	TRIPLES		3070	3720	4260	4920	5580	6230	6770	7010	7460	7910					
480/85R34	LI						142		149								
	SINGLES		3300	3960	4540	5200	5840	6600	7150								
	DUALS		2900	3480	4000	4580	5140	5810	6290								
	TRIPLES		2710	3250	3720	4260	4790	5410	5860								
520/70R38	LI						143		150								
	SINGLES		3300	3960	4680	5200	6000	6600	7400								
	DUALS		2900	3480	4120	4580	5280	5810	6510								
	TRIPLES		2710	3250	3840	4260	4920	5410	6070								
520/85R34	LI						146		154			157	159	162			
	SINGLES		3740	4400	5200	6000	6600	7400	8250	8550	9100	9650	10500				
	DUALS		3290	3870	4580	5280	5810	6510	7260	7520	8010	8490	9240				
	TRIPLES		3070	3610	4260	4920	5410	6070	6770	7010	7460	7910	8610				

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
480/70R30		LI						134		141							
	SINGLES		1180	1400	1650	1900	2120	2360	2575	2725	2900	3075	3350	3550			
	DUALS		1040	1230	1450	1670	1870	2080	2270	2400	2550	2710	2950	3120			
	TRIPLES		970	1150	1350	1560	1740	1940	2110	2230	2380	2520	2750	2910			
480/70R34		LI					136		143			146	149	152	155		
	SINGLES		1250	1500	1750	2000	2240	2500	2725	2900	3000	3250	3550	3875			
	DUALS		1100	1320	1540	1760	1970	2200	2400	2550	2640	2860	3120	3410			
	TRIPLES		1030	1230	1440	1640	1840	2050	2240	2380	2460	2670	2910	3180			
480/70R38		LI					138		145								
	SINGLES		1320	1600	1850	2120	2360	2650	2900								
	DUALS		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES		1080	1310	1520	1740	1940	2170	2380								
480/80R30		LI					139		145								
	SINGLES		1320	1600	1850	2120	2430	2650	2900	3075	3250	3450	3750	4000	4375		
	DUALS		1160	1410	1630	1870	2140	2330	2550	2710	2860	3040	3300	3520	3850		
	TRIPLES		1080	1310	1520	1740	1990	2170	2380	2520	2670	2830	3080	3280	3590		
480/80R38		LI					142		149								
	SINGLES		1500	1800	2060	2360	2650	3000	3250								
	DUALS		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES		1230	1480	1690	1940	2170	2460	2670								
480/80R42		LI					144		151		154						
	SINGLES		1550	1850	2180	2500	2800	3150	3450	3650	3750						
	DUALS		1360	1630	1920	2200	2460	2770	3040	3210	3300						
	TRIPLES		1270	1520	1790	2050	2300	2580	2830	2990	3080						
480/80R46		LI					145		152		155	158					
	SINGLES		1650	1950	2300	2575	2900	3250	3550	3750	3875	4250					
	DUALS		1450	1720	2020	2270	2550	2860	3120	3300	3410	3740					
	TRIPLES		1350	1600	1890	2110	2380	2670	2910	3080	3180	3490					
480/80R50		LI					147		154		157	159					
	SINGLES		1700	2060	2360	2725	3075	3450	3750	3875	4125	4375					
	DUALS		1500	1810	2080	2400	2710	3040	3300	3410	3630	3850					
	TRIPLES		1390	1690	1940	2230	2520	2830	3080	3180	3380	3590					
480/85R34		LI					142		149								
	SINGLES		1500	1800	2060	2360	2650	3000	3250								
	DUALS		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES		1230	1480	1690	1940	2170	2460	2670								
520/70R38		LI					143		150								
	SINGLES		1500	1800	2120	2360	2725	3000	3350								
	DUALS		1320	1580	1870	2080	2400	2640	2950								
	TRIPLES		1230	1480	1740	1940	2240	2460	2750								
520/85R34		LI					146		154		157	159	162				
	SINGLES		1700	2000	2360	2725	3000	3350	3750	3875	4125	4375	4750				
	DUALS		1500	1760	2080	2400	2640	2950	3300	3410	3630	3850	4180				
	TRIPLES		1390	1640	1940	2230	2460	2750	3080	3180	3380	3590	3900				

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
	LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
520/85R38	LI						148	155									
	SINGLES		3860	4680	5520	6150	6950	7850	8550								
	DUALS		3400	4120	4860	5410	6120	6910	7520								
	TRIPLES		3170	3840	4530	5040	5700	6440	7010								
520/85R42	LI						150	157		160	162	165					
	SINGLES		4080	4940	5680	6600	7400	8250	9100	9350	9900	10500	11400				
	DUALS		3590	4350	5000	5810	6510	7260	8010	8230	8710	9240	10030				
	TRIPLES		3350	4050	4660	5410	6070	6770	7460	7670	8120	8610	9350				
520/85R46	LI						151	158									
	SINGLES		4300	5080	6000	6800	7600	8550	9350								
	DUALS		3780	4470	5280	5980	6690	7520	8230								
	TRIPLES		3530	4170	4920	5580	6230	7010	7670								
540/65R24	LI						134	140									
	SINGLES		2600	3080	3640	4080	4680	5080	5520								
	DUALS		2290	2710	3200	3590	4120	4470	4860								
	TRIPLES		2130	2530	2980	3350	3840	4170	4530								
540/65R28	LI						136	142									
	SINGLES		2760	3300	3860	4400	4940	5520	5840								
	DUALS		2430	2900	3400	3870	4350	4860	5140								
	TRIPLES		2260	2710	3170	3610	4050	4530	4790								
540/65R30	LI						137	143		147	150						
	SINGLES		2830	3420	3960	4540	5080	5680	6000	6400	6800	7400					
	DUALS		2490	3010	3480	4000	4470	5000	5280	5630	5980	6510					
	TRIPLES		2320	2800	3250	3720	4170	4660	4920	5250	5580	6070					
540/65R34	LI						140	145		149	152						
	SINGLES		3000	3640	4180	4800	5520	6000	6400	6800	7150	7850					
	DUALS		2640	3200	3680	4220	4860	5280	5630	5980	6290	6910					
	TRIPLES		2460	2980	3430	3940	4530	4920	5250	5580	5860	6440					
540/65R38	LI						141	147									
	SINGLES		3200	3860	4400	5080	5680	6150	6800								
	DUALS		2820	3400	3870	4470	5000	5410	5980								
	TRIPLES		2620	3170	3610	4170	4660	5040	5580								
580/85R42	LI						156	163		166	168						
	SINGLES		4800	5840	6800	7850	8800	9650	10700	11000	11700	12300					
	DUALS		4220	5140	5980	6910	7740	8490	9420	9680	10300	10820					
	TRIPLES		3940	4790	5580	6440	7220	7910	8770	9020	9590	10080					
600/65R28	LI						142	147		152	154						
	SINGLES		3300	3860	4540	5200	5840	6400	6800	7400	7850	8250					
	DUALS		2900	3400	4000	4580	5140	5630	5980	6510	6910	7260					
	TRIPLES		2710	3170	3720	4260	4790	5250	5580	6070	6440	6770					
600/65R34	LI						145	152									
	SINGLES		3520	4300	4940	5680	6400	6950	7600								
	DUALS		3100	3780	4350	5000	5630	6120	6690								
	TRIPLES		2890	3530	4050	4660	5250	5700	6230								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE		INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
520/85R38		LI						148	155								
	SINGLES		1750	2120	2500	2800	3150	3550	3875								
	DUALS		1540	1870	2200	2460	2770	3120	3410								
	TRIPLES		1440	1740	2050	2300	2580	2910	3180								
520/85R42		LI					150	157		160	162	165					
	SINGLES		1850	2240	2575	3000	3350	3750	4125	4250	4500	4750	5150				
	DUALS		1630	1970	2270	2640	2950	3300	3630	3740	3960	4180	4530				
	TRIPLES		1520	1840	2110	2460	2750	3080	3380	3490	3690	3900	4220				
520/85R46		LI					151	158									
	SINGLES		1950	2300	2725	3075	3450	3875	4250								
	DUALS		1720	2020	2400	2710	3040	3410	3740								
	TRIPLES		1600	1890	2230	2520	2830	3180	3490								
540/65R24		LI					134	140									
	SINGLES		1180	1400	1650	1850	2120	2300	2500								
	DUALS		1040	1230	1450	1630	1870	2020	2200								
	TRIPLES		970	1150	1350	1520	1740	1890	2050								
540/65R28		LI					136	142									
	SINGLES		1250	1500	1750	2000	2240	2500	2650								
	DUALS		1100	1320	1540	1760	1970	2200	2330								
	TRIPLES		1030	1230	1440	1640	1840	2050	2170								
540/65R30		LI					137	143		147	150						
	SINGLES		1285	1550	1800	2060	2300	2575	2725	2900	3075	3350					
	DUALS		1130	1360	1580	1810	2020	2270	2400	2550	2710	2950					
	TRIPLES		1050	1270	1480	1690	1890	2110	2230	2380	2520	2750					
540/65R34		LI					140	145		149	152						
	SINGLES		1360	1650	1900	2180	2500	2725	2900	3075	3250	3550					
	DUALS		1200	1450	1670	1920	2200	2400	2550	2710	2860	3120					
	TRIPLES		1120	1350	1560	1790	2050	2230	2380	2520	2670	2910					
540/65R38		LI					141	147									
	SINGLES		1450	1750	2000	2300	2575	2800	3075								
	DUALS		1280	1540	1760	2020	2270	2460	2710								
	TRIPLES		1190	1440	1640	1890	2110	2300	2520								
580/85R42		LI					156	163		166	168						
	SINGLES		2180	2650	3075	3550	4000	4375	4875	5000	5300	5600					
	DUALS		1920	2330	2710	3120	3520	3850	4290	4400	4660	4930					
	TRIPLES		1790	2170	2520	2910	3280	3590	4000	4100	4350	4590					
600/65R28		LI					142	148		152	154						
	SINGLES		1500	1750	2060	2360	2650	2900	3150	3350	3550	3750					
	DUALS		1320	1540	1810	2080	2330	2550	2770	2950	3120	3300					
	TRIPLES		1230	1440	1690	1940	2170	2380	2580	2750	2910	3080					
600/65R34		LI					145	151									
	SINGLES		1600	1950	2240	2575	2900	3150	3450								
	DUALS		1410	1720	1970	2270	2550	2770	3040								
	TRIPLES		1310	1600	1840	2110	2380	2580	2830								

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
	LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
600/65R38	LI						147		153								
	SINGLES		3740	4540	5200	6000	6800	7400	8050	8550	8800	9650	10500	11400			
	DUALS		3290	4000	4580	5280	5980	6510	7080	7520	7740	8490	9240	10030			
	TRIPLES		3070	3720	4260	4920	5580	6070	6600	7010	7220	7910	8610	9350			
600/70R28	LI						145		152		155	157	161	164			
	SINGLES		3640	4300	5080	5680	6400	7150	7850	8250	8550	9100	10200	11000			
	DUALS		3200	3780	4470	5000	5630	6290	6910	7260	7520	8000	8980	9680			
	TRIPLES		2980	3530	4170	4660	5250	5860	6440	6770	7010	7460	8360	9020			
600/70R30	LI						146		152		156	158	162				
	SINGLES		3640	4400	5200	5840	6600	7400	7850	8550	8800	9350	10500				
	DUALS		3200	3870	4580	5140	5810	6510	6910	7520	7740	8230	9240				
	TRIPLES		2980	3610	4260	4790	5410	6070	6440	7010	7220	7670	8610				
620/70R42	LI						153		160		164	166					
	SINGLES		4540	5360	6400	7150	8050	9100	9900	10500	11000	11700					
	DUALS		4000	4720	5630	6290	7080	8010	8710	9240	9680	10300					
	TRIPLES		3720	4400	5250	5860	6600	7460	8120	8610	9020	9590					
620/70R46	LI						155		162		165	167	170	173	175	177	180
	SINGLES		4680	5680	6600	7600	8550	9350	10500	11000	11400	12000	13200	14300	15200	16100	17600
	DUALS		4120	5000	5800	6700	7500	8250	9250	9700	10000	10600	11600	12600	13400	14200	15500
	TRIPLES		3840	4660	5420	6250	7000	7650	8600	9000	9350	9850	10800	11700	12500	13200	14400
620/75R30	LI						150		157		160	163					
	SINGLES		4180	4940	5840	6600	7400	8250	9100	9650	9900	10700					
	DUALS		3680	4350	5140	5810	6510	7260	8010	8490	8710	9420					
	TRIPLES		3430	4050	4790	5410	6070	6770	7460	7910	8120	8770					
650/65R38	LI						151		157		160	163	166				
	SINGLES		4180	5080	5840	6800	7600	8250	9100	9650	9900	10700	11700				
	DUALS		3680	4470	5140	5980	6690	7260	8000	8500	8712	9416	10296				
	TRIPLES		3430	4170	4790	5580	6230	6770	7460	7910	8120	8770	9600				
650/65R42	LI						153		158								
	SINGLES		4400	5360	6150	7150	8050	8800	9350								
	DUALS		3870	4720	5410	6290	7080	7740	8230								
	TRIPLES		3610	4400	5040	5860	6600	7220	7670								
650/75R32	LI						154		160		164	167	169	172			
	SINGLES		4540	5520	6400	7400	8250	9100	9900	10700	11000	12000	12800	13900			
	DUALS		4000	4860	5630	6510	7260	8010	8700	9420	9680	10600	11260	12230			
	TRIPLES		3720	4530	5250	6070	6770	7460	8100	8770	9020	9850	10500	11400			
650/85R38	LI						160		167		170	173					
	SINGLES		5520	6600	7850	8800	9900	11000	12000	12800	13200	14300					
	DUALS		4860	5810	6910	7740	8710	9680	10560	11260	11620	12580					
	TRIPLES		4530	5410	6440	7220	8120	9020	9840	10500	10820	11730					
710/70R38	LI						159		166		169	171					
	SINGLES		5360	6400	7400	8550	9650	10700	11700	12300	12800	13600					
	DUALS		4720	5630	6510	7520	8490	9420	10300	10820	11260	11970					
	TRIPLES		4400	5250	6070	7010	7910	8770	9590	10090	10500	11150					

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
600/65R38	LI							147		153		156	159	162	165		
	SINGLES		1700	2060	2360	2725	3075	3350	3650	3875	4000	4375	4750	5150			
	DUALS		1500	1810	2080	2400	2710	2950	3210	3410	3520	3850	4180	4530			
	TRIPLES		1390	1690	1940	2230	2520	2750	2990	3180	3280	3590	3900	4220			
600/70R28	LI						145		152		155	157	161	164			
	SINGLES		1650	1950	2300	2575	2900	3250	3550	3750	3875	4125	4625	5000			
	DUALS		1450	1720	2020	2270	2550	2860	3120	3300	3410	3630	4070	4400			
	TRIPLES		1350	1600	1890	2110	2380	2670	2910	3080	3180	3380	3800	4100			
600/70R30	LI						146		153		156	158	162				
	SINGLES		1650	2000	2360	2650	3000	3350	3650	3875	4000	4250	4750				
	DUALS		1450	1760	2080	2330	2640	2950	3210	3410	3520	3740	4180				
	TRIPLES		1350	1640	1940	2170	2460	2750	2990	3180	3280	3490	3900				
620/70R42	LI						153		160		164	166					
	SINGLES		2060	2430	2900	3250	3650	4125	4500	4750	5000	5300					
	DUALS		1810	2140	2550	2860	3210	3630	3960	4180	4400	4660					
	TRIPLES		1690	1990	2380	2670	2990	3380	3690	3900	4100	4350					
620/70R46	LI		2120	2575	3000	3450	3875	4250	4750	5000	5150	5450	6000	6500	6900	7300	8000
	SINGLES		1870	2270	2640	3040	3420	3740	4180	4400	4540	4800	5280	5720	6050	6400	7050
	DUALS		1740	2110	2460	2830	3180	3480	3900	4100	4220	4460	4920	5340	5660	5980	6550
	TRIPLES																
620/75R30	LI						150		157		160	163					
	SINGLES		1900	2240	2650	3000	3350	3750	4125	4375	4500	4875					
	DUALS		1670	1970	2330	2640	2950	3300	3630	3850	3960	4290					
	TRIPLES		1560	1840	2170	2460	2750	3080	3380	3590	3690	4000					
650/65R38	LI						151		157		160	163	166				
	SINGLES		1900	2300	2650	3075	3450	3750	4125	4375	4500	4875	5300				
	DUALS		1670	2020	2330	2710	3040	3300	3630	3850	3960	4290	4660				
	TRIPLES		1560	1890	2170	2520	2830	3080	3380	3590	3690	4000	4350				
650/65R42	LI						153		158								
	SINGLES		2000	2430	2800	3250	3650	4000	4250								
	DUALS		1760	2140	2460	2860	3210	3520	3740								
	TRIPLES		1640	1990	2300	2670	2990	3280	3470								
650/75R32	LI						154		160		164	167	169	172			
	SINGLES		2060	2500	2900	3350	3750	4125	4500	4875	5000	5450	5800	6300			
	DUALS		1810	2200	2550	2950	3300	3630	3960	4290	4400	4800	5100	5540			
	TRIPLES		1690	2050	2380	2750	3080	3380	3700	4000	4100	4460	4760	5170			
650/85R38	LI						160		167		170	173					
	SINGLES		2500	3000	3550	4000	4500	5000	5450	5800	6000	6500					
	DUALS		2200	2640	3120	3520	3960	4400	4800	5100	5280	5720					
	TRIPLES		2050	2460	2910	3280	3690	4100	4470	4760	4920	5330					
710/70R38	LI						159		166		169	171					
	SINGLES		2430	2900	3350	3875	4375	4875	5300	5600	5800	6150					
	DUALS		2140	2550	2950	3410	3850	4290	4660	4930	5100	5410					
	TRIPLES		1990	2380	2750	3180	3590	4000	4350	4590	4760	5040					

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION ENGLISH UNITS OF MEASURE (bs@psi)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
710/70R42	LI						160	168		171	173						
	SINGLES		5520	6600	7850	8800	9900	11000	12300	12800	13600	14300					
	DUALS		4860	5810	6910	7740	8710	9680	10820	11260	11970	12580					
	TRIPLES		4530	5410	6440	7220	8120	9020	10090	10500	11150	11730					
710/75R34	LI					159	167		170	172							
	SINGLES		5360	6400	7600	8550	9650	10700	12000	12300	13200	13900					
	DUALS		4720	5630	6690	7520	8490	9420	10560	10820	11620	12230					
	TRIPLES		4400	5250	6230	7010	7910	8770	9840	10090	10820	11400					
750/65R26	LI					153	159		163	166	169						
	SINGLES		4540	5360	6400	7150	8050	8800	9650	10200	10700	11700	12800				
	DUALS		4000	4720	5630	6290	7080	7740	8490	8980	9420	10300	11260				
	TRIPLES		3720	4400	5250	5860	6600	7220	7910	8360	8770	9590	10500				
800/65R32	LI					159	166		169	172							
	SINGLES		5360	6600	7600	8800	9650	10700	11700	12300	12800	13900					
	DUALS		4720	5810	6690	7740	8490	9420	10300	10820	11260	12230					
	TRIPLES		4400	5410	6230	7220	7910	8770	9590	10090	10500	11400					
800/70R38	LI					166	173		176	178	181						
	SINGLES		6400	7600	9100	10200	11700	12800	14300	14800	15700	16500	18200				
	DUALS		5630	6690	8010	8980	10300	11260	12580	13020	13820	14520	16020				
	TRIPLES		5250	6230	7460	8360	9590	10500	11730	12140	12870	13530	14920				
900/50R42	LI					161	168										
	SINGLES		5680	6800	7850	9100	10200	11400	12300								
	DUALS		5000	5980	6910	8010	8980	10030	10820								
	TRIPLES		4660	5580	6440	7460	8360	9350	10090								
900/60R32	LI					163	169		173	176							
	SINGLES		5840	7150	8250	9350	10700	11700	12800	13900	14300	15700					
	DUALS		5140	6290	7260	8230	9420	10300	11260	12230	12580	13820					
	TRIPLES		4790	5860	6770	7670	8770	9590	10500	11400	11730	12870					
900/65R32	LI					166	172		176	178							
	SINGLES		6600	7850	9100	10500	11700	12800	13900	14800	15700	16500					
	DUALS		5810	6910	8010	9240	10300	11260	12230	13020	13820	14520					
	TRIPLES		5410	6440	7460	8610	9590	10500	11400	12140	12870	13530					
900/75R32	LI					172	179		182	184							
	SINGLES		7850	9350	10700	12300	13900	15700	17100	17600	18700	19800					
	DUALS		6910	8230	9420	10820	12230	13820	15050	15490	16460	17420					
	TRIPLES		6440	7670	8770	10090	11400	12870	14020	14430	15330	16240					

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi	Symbol	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
	LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																
710/70R42		LI					160		168		171	173					
	SINGLES		2500	3000	3550	4000	4500	5000	5600	5800	6150	6500					
	DUALS		2200	2640	3120	3520	3960	4400	4930	5100	5410	5720					
	TRIPLES		2050	2460	2910	3280	3690	4100	4590	4760	5040	5330					
710/75R34		LI					159		167		170	172					
	SINGLES		2430	2900	3450	3875	4375	4875	5450	5600	6000	6300					
	DUALS		2140	2550	3040	3410	3850	4290	4800	4930	5280	5540					
	TRIPLES		1990	2380	2830	3180	3590	4000	4470	4590	4920	5170					
750/65R26		LI					153		159		163	166	169				
	SINGLES		2060	2430	2900	3250	3650	4000	4375	4625	4875	5300	5800				
	DUALS		1810	2140	2550	2860	3210	3520	3850	4070	4290	4660	5100				
	TRIPLES		1690	1990	2380	2670	2990	3280	3590	3790	4000	4350	4760				
800/65R32		LI					159		166		169	172					
	SINGLES		2430	3000	3450	4000	4375	4875	5300	5600	5800	6300					
	DUALS		2140	2640	3040	3520	3850	4290	4660	4930	5100	5540					
	TRIPLES		1990	2460	2830	3280	3590	4000	4350	4590	4760	5170					
800/70R38		LI					166		173		176	178	181				
	SINGLES		2900	3450	4125	4625	5300	5800	6500	6700	7100	7500	8250				
	DUALS		2550	3040	3630	4070	4660	5100	5720	5900	6250	6600	7260				
	TRIPLES		2380	2830	3380	3790	4350	4760	5330	5490	5820	6150	6770				
900/50R42		LI					161		168								
	SINGLES		2575	3075	3550	4125	4625	5150	5600								
	DUALS		2270	2710	3120	3630	4070	4530	4930								
	TRIPLES		2110	2520	2910	3380	3790	4220	4590								
900/60R32		LI					166		172		176	178					
	SINGLES		3000	3550	4125	4750	5300	5800	6300	6700	7100	7500					
	DUALS		2640	3120	3630	4180	4660	5100	5540	5900	6250	6600					
	TRIPLES		2460	2910	3380	3900	4350	4760	5170	5490	5820	6150					
900/65R32		LI					166		172		176	178					
	SINGLES		6600	7850	9100	10500	11700	12800	13900	14800	15700	16500					
	DUALS		5810	6910	8010	9240	10300	11260	12230	13020	13820	14520					
	TRIPLES		5410	6440	7460	8610	9590	10500	11400	12140	12870	13530					
900/75R32		LI					172		179		182	184					
	SINGLES		3550	4250	4875	5600	6300	7100	7750	8000	8500	9000					
	DUALS		3120	3740	4290	4930	5540	6250	6820	7040	7480	7920					
	TRIPLES		2910	3490	4000	4590	5170	5820	6360	6560	6970	7380					

RADIAL FARM
BIAS FARM
FRONTS & IMPLEMENTS
FORESTRY & FLOTATION
DISCONTINUED
LOAD & INFLATION TABLES
GENERAL TIRE INFORMATION
WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.



TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE (lbs@psi)

TIRE SIZE	INFLATION psi Symbol	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
		6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
LOAD LIMITS IN LBS., INFLATION PRESSURE IN PSI																
1050/50R25	SINGLES	LI	5840	6950	8050	9350	10500	11700	12800	13600	14300					
	DUALS		5140	6120	7080	8230	9240	10300	11260	11970	12580					
	TRIPLES		4790	5700	6600	7670	8610	9590	10500	11150	11730					

NOTES:

- For shipping purposes, tire inflation pressures may be increased to 30 psi (210 kPa). Inflation pressure must be adjusted to correct operating inflation before placing tires in service.
- For transport service above 20 mph (30 km/h), recommended minimum inflation pressure is 8 psi (60 kPa).
- For tires used in cyclic loading service, see Table F1 on pages 195-196.
- For transport service and operations that do not require sustained high torque, the load limits shown at right at various speeds apply with no change in inflation pressure.

Speed Symbol	Service Speed	% Change to loads in above		
		A8	B	D
A8	Stationary	+130%	+130%	+130%
	15 km/h [10 mph]	+34%	+34%	+34%
	25 km/h [15 mph]	+11%	+11%	+18.5%
	30 km/h [25 mph]	+7%	+7%	+15%
B	40 km/h [25 mph]	None	None	+9.5%
	50 km/h [30 mph]	-	None	+5%
D	65 km/h [40 mph]	-	-	None

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

TABLE B – METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE (kg@kPa)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	kPa		40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
	bar		0.4	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.4	2.8	3.2	3.6	4.0	4.4
LOAD LIMITS IN KG., INFLATION PRESSURE IN kPa																	
	LI					162		169		173							
1050/50R25	SINGLES		2650	3150	3650	4240	4760	5300	5800	6170	6490						
	DUALS		2330	2770	3210	3730	4190	4660	5100	5429.6	5710						
	TRIPLES		2170	2580	3000	3480	3900	4350	4760	5060	5320						

NOTES:

- For shipping purposes, tire inflation pressures may be increased to 30 psi (210 kPa). Inflation pressure must be adjusted to correct operating inflation before placing tires in service.
- For transport service above 20 mph (30 km/h), recommended minimum inflation pressure is 8 psi (60 kPa).
- For tires used in cyclic loading service, see Table F1 on pages 195-196.
- For transport service and operations that do not require sustained high torque, the load limits shown at right at various speeds apply with no change in inflation pressure.

Speed Symbol	Service Speed	% Change to loads in above		
		A8	B	D
A8	Stationary	+130%	+130%	+130%
	15 km/h [10 mph]	+34%	+34%	+34%
	25 km/h [15 mph]	+11%	+11%	+18.5%
	30 km/h [25 mph]	+7%	+7%	+15%
	40 km/h [25 mph]	None	None	+9.5%
B	50 km/h [30 mph]	-	None	+5%
D	65 km/h [40 mph]	-	-	None

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.