



FIRESTONE AG PRODUCT BULLETIN

AD² RADIAL ALL TRACTION DT TIRES

DESCRIPTION: Radial All Traction DT Tires

SIZES: See size chart below. Offered in both IF and VF.

APPLICATIONS: Agriculture equipment



Firestone

FirestoneAg.com

- Available with up to 54" rim diameter, allowing for high row crop clearance.
- Designed with R-1W tread depth, which is approximately 25% deeper in the center than standard R-1 tread, helping to improve wet traction performance.
- IF- and VF-designated tires feature AD² technology, which helps farmers carry heavier loads at the same pressure as standard tires, or the same loads at reduced inflation pressure. This leads to reduced fuel use and reduced soil compaction.

RADIAL ALL TRACTION DT TIRES

Tire Size	Material Number	Load Index	Speed Symbol Rating	Design Rim Width (in.)	Overall Width (in.)	Overall Diameter (in.)	Static Loaded Radius (in.)	Rolling Circum.	Rolling Circum. Index	Bar Height 32nds	Bar Height (in.)	Flat Plate (in. ²)	Max. Load & Infl. (lbs. @ psi)
320/85R24	362-681	122	B	10.00	12.6	45.1	20	137	37	51	1.59	150	3300 @ 23
340/85R24	362-698	125	B	11.00	13.5	47.0	21	143	38	53	1.66	165	3640 @ 23
380/85R24	362-715	131	B	12.00	15.0	49.0	22	148	38	55	1.72	180	4300 @ 23
VF620/75R26	001-603	172	B	20.00	24.5	62.1	27	187	-	66	2.10	476	13900 @ 35
VF750/65R26	000-556	177	B	25.00	30.3	64.0	27	190	-	67	2.09	534	16100 @ 35
750/65R26	376-791	166	B	25.00	29.2	64.6	29	192	-	67	2.09	453	11700 @ 35
750/65R26	000-906	169	B	25.00	30.1	64.1	29	192	-	67	2.09	453	12800 @ 41
480/70R28	351-563	140	B	15.00	19.1	56.5	25	168	41	55	1.72	245	5520 @ 23
600/65R28	360-058	147	B	18.00	23.0	58.7	26	174	42	65	2.03	330	6800 @ 23
600/65R28	371-266	154	B	18.00	23.0	58.7	26	174	42	65	2.03	330	8250 @ 35
600/70R28	000-907	164	B	18.00	23.8	60.7	27	178	42	65	2.03	355	11000 @ 46
VF600/70R28CFO	004-927	173	B	21.00	24.4	60.9	27	181	-	65	2.04	390	14300 @ 41
VF600/70R28	001-602	173	B	21.00	23.7	61.1	27	181	-	65	2.03	389	14300 @ 41
380/85R30	364-551	135	B	13.00	15.5	55.8	26	167	41	61	1.91	190	4800 @ 23
420/90R30	364-602	145	B	15.00	17.7	58.8	27	174	42	62	1.94	235	6400 @ 29
480/70R30	355-569	152	B	15.00	19.0	59.7	27	177	42	55	1.72	275	7850 @ 46
480/80R30	362-732	145	B	15.00	18.9	60.6	27	179	42	62	1.94	290	6400 @ 23
IF600/70R30	375-703	159	B	20.00	24.4	62.6	27	187	43	64	2.00	425	9650 @ 29
600/70R30	003-778	152	A8	24.00	24.0	62.8	28	#	#	65	2.03	370	7850 @ 23
600/70R30	360-163	152	B	20.00	24.0	62.8	28	187	43	65	2.03	370	7850 @ 23
600/70R30	362-307	162	B	20.00	24.0	62.9	28	187	43	65	2.03	370	10500 @ 41
IF620/75R30	377-539	164	D	21.00	24.6	66.6	28	198	44	67	2.09	403	11000 @ 23
650/75R32	382-486	172	D	21.00	26.0	70.2	32	210	45	70	2.19	450	13900 @ 46
650/75R32	361-925	172	B	21.00	25.6	70.5	32	210	45	70	2.19	450	13900 @ 46
800/65R32	382-469	172	D	25.00	32.6	72.1	33	216	46	74	2.31	575	13900 @ 35



FIRESTONE AG PRODUCT BULLETIN

AD²
RADIAL ALL TRACTION DT TIRES

RADIAL ALL TRACTION DT TIRES

Tire Size	Material Number	Load Index	Speed Symbol Rating	Design Rim Width (in.)	Overall Width (in.)	Overall Diameter (in.)	Static Loaded Radius (in.)	Rolling Circum.	Rolling Circum-Index	Bar Height 32nds	Bar Height (in.)	Flat Plate (in. ²)	Max. Load & Infl. (lbs. @ psi)
800/65R32	357-685	172	B	27.00	32.1	73.3	33	216	46	74	2.31	575	13900 @ 35
IF900/75R32CFO	004-459	178	B	30.00	36.6	84.5	36	253	49	82	2.56	895	16500 @ 17
900/75R32	375-958	184	B	30.00	37.0	85.5	38	253	49	82	2.56	761	19800 @ 35
380/85R34	364-585	137	B	13.00	15.5	59.8	28	179	42	61	1.91	210	5080 @ 23
IF420/85R34	374-513	152	B	14.00	16.3	62.4	28	187	43	59	1.84	283	7850 @ 29
420/85R34	360-155	147	B	13.00	16.5	62.6	28	187	43	59	1.84	245	6800 @ 35
420/85R34	372-133	147	B	13.00	16.5	62.6	28	187	43	59	1.84	245	6800 @ 35
IF580/80R34	381-585	172	B	20.00	23.5	70.0	31	209	45	73	2.28	415	13900 @ 41
380/80R38	360-171	142	B	12.00	15.3	62.8	29	187	43	57	1.78	230	5840 @ 35
IF380/80R38	378-627	149	B	12.00	15.3	62.8	29	187	43	57	1.78	230	6950 @ 35
IF420/85R38	378-882	153	B	14.00	16.7	66.1	30	198	44	59	1.84	297	8050 @ 29
IF710/70R38	378-219	178	B	25.00	29.6	76.2	34	227	47	74	2.31	580	16500 @ 35
710/70R38	355-542	166	B	23.00	28.3	77.0	34	227	47	74	2.31	505	11700 @ 23
620/70R42	356-271	160	B	20.00	24.6	76.2	34	226	47	66	2.06	475	9900 @ 23
620/70R42	374-479	166	B	20.00	24.6	76.2	34	226	47	66	2.06	475	11700 @ 35
IF710/70R42	373-697	179	B	25.00	29.4	80.2	35	240	48	74	2.31	590	17100 @ 35
IF710/70R42CFO	004-592	179	B	25.00	29.4	80.2	35	240	48	74	2.31	590	17100 @ 35
710/70R42	003-780	168	B	23.00	28.5	80.9	36	#	#	73	2.28	530	12300 @ 23
710/70R42	358-320	168	B	23.00	28.5	80.9	36	240	48	74	2.31	530	12300 @ 23
IF710/75R42	378-542	181	B	25.00	30.5	84.4	37	253	49	77	2.41	672	18200 @ 35
320/90R54	358-339	149	B	10.00	12.4	76.7	36	233	47	56	1.75	215	7150 @ 46