

E-3, L-3



The Super Rock Grip™ bias tire offers a wide base for added stability and rubber compounds designed for wear resistance on improved surfaces in dock and in rail yard applications.



**LOADERS** 

GRADERS

**SCRAPERS** 

**CONTAINER HANDLERS** 

## SPECIALIZED FEATURES

- 1 NON-DIRECTIONAL ROCK TREAD PATTERN for excellent traction and flotation
- 2 EXTRA TOUGH TREAD COMPOUND for cut and impact protection
- **WIDEBASE SIZES** offer wide cross section and tread









CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT." [LBS]	<b>OTD</b> " [32"]	OVERALL DIAMETER [IN / MM]	OVERALL WIDTH [IN / MM]
LARGE TUBELESS	16.00-25	28	-	E-3	413518	460	36	-	-
	26.5-25	44	IDU	L-3	480136	1045	44	-	-
LARGE TUBELESS	29.5-29	28	STC	E-3	401889	1178	48	-	-
	29.5-29	34	STC	E-3	401625	1221	48	-	-
	33.25-29	32	-	E-3	280138	1610	57	-	-
	37.5-33	42	STC	E-3	401501	2224	58	-	-
	29.5-35	34	STC	E-3	401668	1319	48	-	-
	33.25-35	38	-	E-3	410241	1870	53	-	-
	37.25-35	36	-	E-3	413461	2241	62	-	-
	37.5-39	52	-	E-3	412546	2781	60	-	-
GIANT TUBELESS	18.00-49	32	STC	E-3	401560	1099	34	-	-
	30-56.5	48	-	E-3	413127	2441	53	-	-

Actual specifications may vary depending on the tire produced. Off-road tire limited warranty information is available from your Bridgestone representative or dealer.

