

TABLE P – IRRIGATION TIRES AT CREEP SPEED*

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES					
	psi	18	21	22	24	26	31	34
	kPa	120	145	150	170	180	215	235
11.2-24 (4 Ply)	lbs			3480				
	kg			1580				
11.2-24 (6 Ply)	lbs							4410
	kg							2000
14.9-24 (4 Ply)	lbs	5060						
	kg	2295						
14.9-24 (6 Ply)	lbs					6330		
	kg					2870		
16.9-24 (6 Ply)	lbs				7220			
	kg				3275			
16.9-24 (8 Ply)	lbs						8610	
	kg						3905	
18.4-26 (6 Ply)	lbs		8360					
	kg		3790					
11.2-38 (4 Ply)	lbs				4400			
	kg				2000			
12.4-38 (4 Ply)	lbs		4935					
	kg		2240					
290/85D38 132 Load Index	lbs				4400			
	kg				2000			
380/85D24 145 Load Index	lbs					6400		
	kg					2900		

*Creep speed is a travel rate of not more than 200 feet (61 meters) in a 30-minute period.

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.