

# TABLE E – DIAGONAL (BIAS) PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

TIRE TYPE NOMENCLATURE		MAX SPEED
TRA	TIRE TYPE	SPEED INDEX
		A8
R-1	Drive Wheel, Regular Tread	25 mph
R-2	Cane & Rice, Drive Wheel, Deep Tread	25 mph
R-3	Drive Wheel, Shallow Tread	25 mph
R-4	Industrial Tractor, Drive Wheel, Intermediate Tread	25 mph

## TIRES USED AS SINGLES BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi		12	14	16	18	20	22	24	26	28	30	32				
	kPa		80	100	110	120	140	150	170	180	190	210	220				
7.5-22	lbs.		990	1100	1170	1280	<b>1360 (4)</b>										
	kg		450	500	530	580	<b>615 (4)</b>										
8.3-16	lbs.		640	715	760	825	880	<b>935 (4)</b>	965	1020	1070	1100	1140				1200@34 (6) psi
	kg		290	325	345	375	400	<b>425 (4)</b>	437	462	487	500	515				545@230 (6) kPa
8.3-22	lbs.		785	910	965	990	1100	<b>1170 (4)</b>	1230	1280	1320	1390	1430				1760@36 (6) psi
	kg		355	412	437	450	500	<b>530 (4)</b>	560	580	600	630	650				800@250 (6) kPa
8.3-24	lbs.		880	965	1020	1100	1170	<b>1230 (4)</b>									
	kg		400	437	462	500	530	<b>560 (4)</b>									
9.5-16	lbs.		825	910	965	1050	<b>1100 (4)</b>	1170	1230	1280	1360	<b>1390 (6)</b>					
	kg		375	412	437	475	<b>500 (4)</b>	530	560	580	615	<b>630 (6)</b>					
9.5-22	lbs.		990	1140	1200	1230	<b>1360 (4)</b>	1430	1520	1570	1650	1710	<b>1760 (6)</b>				
	kg		450	515	545	560	<b>615 (4)</b>	650	690	710	750	775	<b>800 (6)</b>				
9.5-24	lbs.		1100	1200	1280	1390	<b>1480 (4)</b>	1570	1650	1710	1820	<b>1870 (6)</b>					
	kg		500	545	580	630	<b>670 (4)</b>	710	750	775	825	<b>850 (6)</b>					
9.5-32	lbs.		1230	1360	1480	1570	<b>1650 (4)</b>	1760	1870	1930	2040	<b>2090 (6)</b>					
	kg		560	615	670	710	<b>750 (4)</b>	800	850	875	925	<b>950 (6)</b>					
9.5-36	lbs.		1320	1430	1570	1650	<b>1760 (4)</b>										
	kg		600	650	710	750	<b>800 (4)</b>										
9.5-42	lbs.		1430	1570	1650	1820	<b>1930 (4)</b>	2040	2150	2270	2340	<b>2400 (6)</b>	2540				2910@40 (8) psi 3200@48 (10) psi
	kg		650	710	750	825	<b>875 (4)</b>	925	975	1030	1060	<b>1090 (6)</b>	1150				1320@280 (8) kPa 1450@330 (10) kPa
11.2-24	lbs.		1320	1430	1570	<b>1650 (4)</b>	1760	1870	1980	<b>2090 (6)</b>	2150	2270	2340	<b>2540@36 (8) psi</b>	<b>2830@44 (10) psi</b>		
	kg		600	650	710	<b>750 (4)</b>	800	850	900	<b>950 (6)</b>	975	1030	1060	<b>1150@250 (8) kPa</b>	<b>1285@300 (10) kPa</b>		
11.2-28	lbs.		1390	1520	1650	<b>1760 (4)</b>	1930	1980	2090	<b>2200 (6)</b>							
	kg		630	690	750	<b>800 (4)</b>	875	900	950	<b>1000 (6)</b>							
11.2-36	lbs.		1570	1760	1870	<b>2040 (4)</b>											
	kg		710	800	850	<b>925 (4)</b>											
11.2-38	lbs.		1650	1760	1930	<b>2090 (4)</b>	2200	2340	2470	2540 (6)							
	kg		750	800	875	<b>950 (4)</b>	1000	1060	1120	1150 (6)							
12.4-16	lbs.		1200	1320	<b>1430 (4)</b>	1520	1650	1710	<b>1820 (6)</b>	1930	1980	2090	2150 (8)				2760@48 (12) psi
	kg		545	600	<b>650 (4)</b>	690	750	775	<b>825 (6)</b>	875	900	950	975 (8)				1250@330 (12) kPa
12.4-24	lbs.		1570	1710	<b>1870 (4)</b>	1980	2150	2270	<b>2400 (6)</b>	2470	2600	2680	2830 (8)				3520@48 (12) psi
	kg		710	775	<b>850 (4)</b>	900	975	1030	<b>1090 (6)</b>	1120	1180	1215	1285 (8)				1600@330 (12) kPa
12.4-28	lbs.		1710	1870	<b>1980 (4)</b>	2150	2270	2400	<b>2540 (6)</b>								
	kg		775	850	<b>900 (4)</b>	975	1030	1090	<b>1150 (6)</b>								

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM  
 BIAS FARM  
 FRONTS & IMPLEMENTS  
 FORESTRY & FLOTATION  
 DISCONTINUED  
 LOAD & INFLATION TABLES  
 GENERAL TIRE INFORMATION  
 WARRANTY

# TABLE E — DIAGONAL (BIAS) PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

## TIRES USED AS SINGLES BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES												
	psi		12	14	16	18	20	22	24	26	28	32			
	kPa		80	100	110	120	140	150	170	180	190	220			
12.4-36	lbs.		1930	2090	<b>2270 (4)</b>	2400	2540	2680	<b>2830 (6)</b>	3000	3080	<b>3420 (8)</b>			<b>3860 @ 40 (10) psi</b>
	kg		875	950	<b>1030 (4)</b>	1090	1150	1215	<b>1285 (6)</b>	1360	1400	<b>1550 (8)</b>			<b>1750 @ 280 (10) kPa</b>
12.4-38	lbs.		1980	2150	<b>2340 (4)</b>	2470	2600	2760	<b>2910 (6)</b>			<b>3520 (8)</b>	<b>4400 @ 48 (12) psi</b>	<b>4800 @ 56 (14) psi</b>	
	kg		900	975	<b>1060 (4)</b>	1120	1180	1250	<b>1320 (6)</b>			<b>1600 (8)</b>	<b>2000 @ 330 (12) kPa</b>	<b>2180 @ 385 (14) kPa</b>	
12.4-42	lbs.		2040	2270	<b>2470 (4)</b>	2600	2760	2910	<b>3080 (6)</b>	3200	3420	<b>3640 (8)</b>		<b>4180 @ 40 (10) psi</b>	
	kg		925	1030	<b>1120 (4)</b>	1180	1250	1320	<b>1400 (6)</b>	1450	1550	<b>1650 (8)</b>		<b>1900 @ 280 (10) kPa</b>	
13.6-16	lbs.		1430	<b>1570 (4)</b>											
	kg		650	<b>710 (4)</b>											
13.6-24	lbs.		*1870	<b>2040 (4)</b>	2200	2340	2540	<b>2680 (6)</b>	2830	2910	<b>3080 (8)</b>				
	kg		*850	<b>925 (4)</b>	1000	1060	1150	<b>1215 (6)</b>	1285	1320	<b>1400 (8)</b>				
13.6-26	lbs.		1930	<b>2090 (4)</b>	2270	2470	2600	<b>2760 (6)</b>	2910	3000	<b>3200 (8)</b>				
	kg		875	<b>950 (4)</b>	1030	1120	1180	<b>1250 (6)</b>	1320	1360	<b>1450 (8)</b>				
13.6-28	lbs.		*1980	<b>2200 (4)</b>	2340	2540	2680	<b>2830 (6)</b>	3000	3080	<b>3300 (8)</b>	3520	<b>3740 @ 36 (10) psi</b>	<b>4180 @ 42 (12) psi</b>	
	kg		*900	<b>1000 (4)</b>	1060	1150	1215	<b>1285 (6)</b>	1360	1400	<b>1500 (8)</b>	1600	<b>1700 @ 250 (10) kPa</b>	<b>1900 @ 290 (12) kPa</b>	
13.6-36	lbs.		*2270	<b>2470 (4)</b>	2680	2830	3000	<b>3200 (6)</b>							
	kg		*1030	<b>1120 (4)</b>	1215	1285	1360	<b>1450 (6)</b>							
13.6-38	lbs.		2340	<b>2540 (4)</b>	2760	2910	3080	<b>3300 (6)</b>							
	kg		1060	<b>1150 (4)</b>	1250	1320	1400	<b>1500 (6)</b>							
13.6-46	lbs.		2540	<b>2830 (4)</b>	3000	3200	3420	<b>3640 (6)</b>	3860	4080	4180 (8)				
	kg		1150	<b>1285 (4)</b>	1360	1450	1550	<b>1650 (6)</b>	1750	1850	1900 (8)				
14.9-24	lbs.		*2200	<b>2400 (4)</b>	2600	2830	<b>3000 (6)</b>	3200	3300	<b>3520 (8)</b>	3640	3960		<b>4400 @ 38 (12) psi</b>	
	kg		*1000	<b>1090 (4)</b>	1180	1285	<b>1360 (6)</b>	1450	1500	<b>1600 (8)</b>	1650	1800		<b>2000 @ 260 (12) kPa</b>	
14.9-26	lbs.		*2270	2540	2680	2910	<b>3080 (6)</b>	3300	3420	3640	3740	<b>4080(10)</b>			
	kg		*1030	1150	1215	1320	<b>1400 (6)</b>	1500	1550	1650	1700	<b>1850(10)</b>			
14.9-28	lbs.		*2340	2600 (4)	2830	3000	<b>3200 (6)</b>	3420	3520	<b>3740 (8)</b>	3860	<b>4180(10)</b>			
	kg		*1060	1180 (4)	1285	1360	<b>1450 (6)</b>	1550	1600	<b>1700 (8)</b>	1750	<b>1900(10)</b>			
14.9-30	lbs.		*2470	2680	2910	3080	<b>3300 (6)</b>	3520	3640	<b>3860 (8)</b>	3960	<b>4300(10)</b>			
	kg		*1120	1215	1320	1400	<b>1500 (6)</b>	1600	1650	<b>1750 (8)</b>	1800	<b>1950(10)</b>			
14.9-38	lbs.		*2760	3000	3300	3520	<b>3740 (6)</b>	3960	4180	<b>4300 (8)</b>	4540	<b>4940(10)</b>		<b>5360 @ 38 (12) psi</b>	
	kg		*1250	1360	1500	1600	<b>1700 (6)</b>	1800	1900	<b>1950 (8)</b>	2060	<b>2240(10)</b>		<b>5840 @ 44 (14) psi</b>	
15.5-38	lbs.		*2600	2830	3080	3300	<b>3520 (6)</b>	3740	3860	<b>4080 (8)</b>					
	kg		*1180	1285	1400	1500	<b>1600 (6)</b>	1700	1750	<b>1850 (8)</b>					
16.9-24	lbs.		*2680	*2910	3200	<b>3420 (6)</b>	3640	3860	<b>4080 (8)</b>	4300	<b>4400(10)</b>				
	kg		*1215	*1320	1450	<b>1550 (6)</b>	1650	1750	<b>1850 (8)</b>	1900	<b>2000(10)</b>				
16.9-26	lbs.		*2760	*3080	3300	<b>3520 (6)</b>	3740	3960	4180	4400	<b>4540(10)</b>				
	kg		*1250	*1400	1500	<b>1600 (6)</b>	1700	1800	1900	2000	<b>2060(10)</b>				
16.9-28	lbs.		*2910	*3200	3420	<b>3640 (6)</b>	3860	4080	<b>4300 (8)</b>	4540	<b>4680(10)</b>				
	kg		*1320	*1450	1550	<b>1650 (6)</b>	1750	1850	<b>1950 (8)</b>	2060	<b>2120(10)</b>				
16.9-30	lbs.		*3000	*3300	3520	<b>3740 (6)</b>	3960	4180	<b>4400 (8)</b>	4680	<b>4940(10)</b>			<b>5520 @ 34 (12) psi</b>	
	kg		*1360	*1500	1600	<b>1700 (6)</b>	1800	1900	<b>2000 (8)</b>	2120	<b>2240(10)</b>			<b>2500 @230 (12) kPa</b>	
16.9-34	lbs.		*3200	*3420	3740	<b>3960 (6)</b>	4300	4540	<b>4680 (8)</b>	4940	<b>5200(10)</b>				
	kg		*1450	*1550	1700	<b>1800 (6)</b>	1950	2060	<b>2120 (8)</b>	2240	<b>2360(10)</b>				
16.9-38	lbs.		*3300	*3640	3960	<b>4180 (6)</b>	4540	4800	<b>4940 (8)</b>						
	kg		*1500	*1650	1800	<b>1900 (6)</b>	2060	2180	<b>2240 (8)</b>						

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

# TABLE E — DIAGONAL (BIAS) PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

## TIRES USED AS SINGLES BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES											
	psi		12	14	16	18	20	22	24	26	28	30		32
	kPa		80	100	110	120	140	150	170	180	190	210		220
18.4-16.1	lbs.	*2150	*2340	<b>2540 (6)</b>	2680	<b>2910 (8)</b>	3080	3200	<b>3300 (10)</b>					
	kg	*975	*1060	<b>1150 (6)</b>	1215	<b>1320 (8)</b>	1400	1450	<b>1500 (10)</b>					
18.4-26	lbs.	*3300	*3640	<b>3960 (6)</b>	4180	<b>4540 (8)</b>	4800	4940	<b>5200 (10)</b>	5520	5680	<b>5840 (12)</b>		
	kg	*1500	*1650	<b>1800 (6)</b>	1900	<b>2060 (8)</b>	2180	2240	<b>2360 (10)</b>	2500	2575	<b>2650 (12)</b>		
18.4-28	lbs.	*3420	*3740	<b>4080 (6)</b>	4400	<b>4680 (8)</b>	4940	5200	<b>5360 (10)</b>	5680	5840	<b>6150 (12)</b>		
	kg	*1550	*1700	<b>1850 (6)</b>	2000	<b>2120 (8)</b>	2240	2360	<b>2430 (10)</b>	2575	2650	<b>2800 (12)</b>		
18.4-30	lbs.	*3520	*3860	<b>4180 (6)</b>	4540	<b>4800 (8)</b>	5080	5360	<b>5520 (10)</b>	5840	6150	<b>6400 (12)</b>		
	kg	*1600	*1750	<b>1900 (6)</b>	2060	<b>2180 (8)</b>	2300	2430	<b>2500 (10)</b>	2650	2800	<b>2900 (12)</b>		
18.4-34	lbs.	*3740	*4180	<b>4400 (6)</b>	4800	<b>5080 (8)</b>	5360	5680	6000	6150	6400	<b>6600 (12)</b>		
	kg	*1700	*1900	<b>2000 (6)</b>	2180	<b>2300 (8)</b>	2430	2575	2725	2800	2900	<b>3000 (12)</b>		
18.4-38	lbs.	*3960	*4400	<b>4680 (6)</b>	5080	<b>5360 (8)</b>	5680	6000	<b>6400 (10)</b>	6600	6800	<b>7150 (12)</b>	<b>7600 @ 36 (14) psi</b>	
	kg	*1800	*2000	<b>2120 (6)</b>	2300	<b>2430 (8)</b>	2575	2725	<b>2900 (10)</b>	3000	3075	<b>3250 (12)</b>	<b>3450@250 (14) kPa</b>	
18.4-42	lbs.	*4180	*4680	4940	5360	<b>5680 (8)</b>	6000	6400	<b>6600 (10)</b>	6950	7150	<b>7400 (12)</b>		
	kg	*1900	*2120	2240	2430	<b>2575 (8)</b>	2725	2900	<b>3000 (10)</b>	3150	3250	<b>3350 (12)</b>		
18.4-46	lbs.	*4400	*4800	5200	5680	6000	6400	6600	6950	7400	7600	7850	<b>8550 @ 36 (14) psi</b>	
	kg	*2000	*2180	2360	2575	2725	2900	3000	3150	3350	3450	3550	<b>3450@250 (14) kPa</b>	
20.8-34	lbs.	*4540	*4940	5360	<b>5840 (8)</b>	6150	<b>6600 (10)</b>							
	kg	*2060	*2240	2430	<b>2650 (8)</b>	2800	<b>3000 (10)</b>							
20.8-38	lbs.	*4800	*5360	5680	<b>6150 (8)</b>	6600	<b>6950 (10)</b>	7150	7600	<b>7850 (12)</b>	8250	<b>8550 (14)</b>		
	kg	*2180	*2430	2575	<b>2800 (8)</b>	3000	<b>3150 (10)</b>	3250	3450	<b>3550 (12)</b>	3750	<b>3875 (14)</b>		
20.8-42	lbs.	*5080	*5520	6000	6400	6950	<b>7400 (10)</b>	7600	8050	<b>8550 (12)</b>	8800	<b>9100 (14)</b>		
	kg	*2300	*2500	2725	2900	3150	<b>3350 (10)</b>	3450	3650	<b>3875 (12)</b>	4000	<b>4125 (14)</b>		
23.1-26	lbs.	*4800	*5200	<b>5680 (8)</b>	6000	<b>6400 (10)</b>	6800	<b>7150 (12)</b>	7600	<b>7850 (14)</b>				
	kg	*2180	*2360	<b>2575 (8)</b>	2725	<b>2900 (10)</b>	3075	<b>3250 (12)</b>	3450	<b>3550 (14)</b>				
23.1-30	lbs.	*5080	*5520	<b>6000 (8)</b>	6400	<b>6800 (10)</b>		<b>7600 (12)</b>						
	kg	*2300	*2500	<b>2725 (8)</b>	2900	<b>3075 (10)</b>		<b>3450 (12)</b>						
23.1-34	lbs.	*5360	*5840	<b>6400 (8)</b>	6800	<b>7400 (10)</b>								
	kg	*2430	*2650	<b>2900 (8)</b>	3075	<b>3350 (10)</b>								
24.5-32	lbs.	*5840	*6400	6800	7400	<b>7850 (10)</b>	8250	<b>8800 (12)</b>	9100	<b>9650 (14)</b>		<b>10400(16)</b>		
	kg	*2650	*2900	3075	3350	<b>3550 (10)</b>	3750	<b>4000 (12)</b>	4125	<b>4375 (14)</b>		<b>4725(16)</b>		
420.70-24	lbs.	2340	2540	<b>2760 (6)</b>	2910	3080	<b>3300 (8)</b>	3520	<b>3640 (10)</b>					
	kg	1060	1150	<b>1250 (6)</b>	1320	1400	<b>1500 (8)</b>	1600	<b>1650 (10)</b>					
17.5L-24	lbs.	2600	2830	<b>3080 (6)</b>	3300	3520	<b>3640 (8)</b>	3860	4080	<b>4180 (10)</b>				
	kg	1180	1285	<b>1400 (6)</b>	1500	1600	<b>1650 (8)</b>	1750	1850	<b>1900 (10)</b>				
19.5L-24	lbs.	3080	3420	3640	3860	<b>4180 (8)</b>	4400	<b>4680 (10)</b>	4800	5080	<b>5200 (12)</b>			
	kg	1400	1550	1650	1750	<b>1900 (8)</b>	2000	<b>2120 (10)</b>	2180	2300	<b>2360 (12)</b>			
21L-28	lbs.	3860	4180 (6)	4540	<b>4800 (8)</b>	5200	<b>5560 (10)</b>	5840	6000	<b>6150 (12)</b>	6600	<b>6800 (14)</b>		
	kg	1750	1900 (6)	2060	<b>2180 (8)</b>	2360	<b>2500 (10)</b>	2650	2725	<b>2800 (12)</b>	3000	<b>3075 (14)</b>		
21.5L-16.1	lbs.	<b>2760 (6)</b>	3000	3200	<b>3420 (8)</b>	3640	<b>3860 (10)</b>							
	kg	<b>1250 (6)</b>	1360	1450	<b>1550 (8)</b>	1650	<b>1750 (10)</b>							
24L-26	lbs.	<b>4300 (6)</b>	4800	<b>5080 (8)</b>	5520	<b>5840 (10)</b>	6150	<b>6600 (12)</b>						
	kg	<b>1950 (6)</b>	2180	<b>2300 (8)</b>	2500	<b>2650 (10)</b>	2800	<b>3000 (12)</b>						
28L-26	lbs.	5520	6000	6600	<b>6950 (10)</b>	<b>7400 (12)</b>	7850	<b>8250 (14)</b>	8800	<b>9100 (16)</b>				
	kg	2500	2725	3000	<b>3150 (10)</b>	<b>3350 (12)</b>	3560	<b>3740 (14)</b>	4000	<b>4125 (16)</b>				
30.5L-32	lbs.	<b>6950 (8)</b>	7600	<b>8250 (10)</b>	8800	<b>9350 (12)</b>	<b>9900 (14)</b>	10500	<b>11000(16)</b>					
	kg	<b>3150 (8)</b>	3450	<b>3750 (10)</b>	4000	<b>4250 (12)</b>	<b>4500 (14)</b>	4750	<b>5000 (16)</b>					

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.

RADIAL FARM  
BIAS FARM  
FRONTS & IMPLEMENTS  
FORESTRY & FLOTATION  
DISCONTINUED  
LOAD & INFLATION TABLES  
GENERAL TIRE INFORMATION  
WARRANTY

# TABLE E — DIAGONAL (BIAS) PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

## TIRES USED AS SINGLES BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES										
	psi		12	14	16	18	20	22	24	26	28	30	32
	kPa		80	100	110	120	140	150	170	180	190	210	220
35.5L-32	lbs.		9350	<b>10200 (10)</b>	<b>11000 (12)</b>	<b>11700 (14)</b>	12800	<b>13200 (16)</b>	<b>13900 (18)</b>	14800	<b>15200 (20)</b>	<b>16100 (22)</b>	<b>16500 (24)</b>
	kg		4250	<b>4625 (10)</b>	<b>5000 (12)</b>	<b>5300 (14)</b>	5800	<b>6000 (16)</b>	<b>6300 (18)</b>	6700	<b>6900 (20)</b>	<b>7300 (22)</b>	<b>7500 (24)</b>

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
	psi		23	26	29	32	35	38	41	44	46	49	52	58	61	64
	kPa		160	180	200	220	240	260	280	300	320	340	360	400	420	440
520/85D38	LI		<b>155</b>		<b>158</b>		<b>160</b>		<b>164</b>		<b>167</b>		<b>169</b>	<b>170</b>		<b>173</b>
	lbs.		<b>8550</b>	9100	<b>9350</b>	9650	<b>9900</b>	10500	<b>11000</b>	11400	<b>12000</b>	12300	<b>12800</b>	<b>13200</b>	13900	<b>14300</b>
	kg		<b>3875</b>	4125	<b>4250</b>	4375	<b>4500</b>	4750	<b>5000</b>	5150	<b>5450</b>	5600	<b>5800</b>	<b>6000</b>	6300	<b>6500</b>

### NOTES:

- Figures in parentheses denote ply rating for which boldface loads and inflations are maximum.
- For shipping purposes, tire inflation pressures may be increased to 30 psi (210 kPa). Consult tire manufacturer for minimum tire shipping pressure. Inflation pressure must be reduced to operating inflation before the machine is removed from the carrier.
- When used as duals, tire loads must be reduced 12%. (Multiply figures in above table at .88.)
- When used as triples, tire loads must be reduced 18%. Multiply figures in above table by .82.)
- For R-3 tires used in free rolling service at speeds up to 10 mph (15 km/h), maximum above loads may be increased 50% with a 4 psi (30 kPa) increase in inflation pressure.
- For R-4 tires in transport service, see Table G, page 142.
- The above loads are also applicable to equipment, including hillside combines, operating on slopes above 11° (20% grade). Load adjustments below 20 mph (30 km/h) do not apply.
- For cyclic loading field service, see Table F2 on page 138. For tire sizes not shown, see Note 4 on page 140.
- For R-1, R-2 and R-3 tires in transport service and operations that do not require sustained high torque, the load limits shown at right at various speeds apply.

MAX. SPEED	% CHANGE IN ABOVE LOADS	% CHANGE IN INFL. PRESSURE
Stationary	+200%	30%
10 mph (15 km/h)	+34% (except hillside combines)	None
15 mph (25 km/h)	+22% (except hillside combines)	None
20 mph (30 km/h)	+11%	None
25 mph (40 km/h)	Same As Table	None

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.