

TABLE O – FARM IMPLEMENT HIGHWAY SPECIAL (F1) TIRES FOR TOWED HIGHWAY AND AGRICULTURAL SERVICE

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION MAXIMUM SPEED 62 MPH (100 KM/H)

TIRE SIZE	INFLATION		LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
	psi		20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
	kPa		140	170	210	240	280	310	340	380	410	450	480	520	550	590	620
9.5L-15FI	lbs	1390	1610	1760 (B)	1930	2090	2270 (C)	2400	2540	2680 (D)	2830	2910	3080 (E)				
	kg	630	730	800 (B)	875	950	1030 (C)	1090	1150	1215 (D)	1285	1320	1400 (E)				
11L-15FI	lbs	1650	1870	2080 (B)	2270	2470	2600 (C)	2830	3000	3080 (D)	3300	3420	3520	3650	3800	3960 (F)	
	kg	750	850	950 (B)	1030	1120	1180 (C)	1285	1360	1400 (D)	1500	1550	1600	1660	1720	1800 (F)	
12.5L-15FI	lbs	1930	2200	2470 (B)	2680	2910	3080 (C)	3300	3520	3740 (D)	3860	4080	4180	4340	4500	4680 (F)	
	kg	875	1000	1120 (B)	1215	1320	1400 (C)	1500	1600	1700 (D)	1750	1850	1900	1970	2040	2120 (F)	

NOTES:

1. This load and inflation table is for FI tires only.
2. Letters in parentheses denote load range for which boldface loads and inflations are maximum.
3. For service at maximum speed of 30 mph (50 km/h) and below, loads may be increased by 20% with no change to the inflation pressure.

RADIAL FARM

BIAS FARM

FRONTS & IMPLEMENTS

FORESTRY & FLOTATION

DISCONTINUED

LOAD & INFLATION TABLES

GENERAL TIRE INFORMATION

WARRANTY

FOR RIM AND WHEEL LOAD INFORMATION, SEE IMPORTANT NOTES ON PAGES 168-172.